

County Surveyor's Record, Douglas County, Oregon

Corrective Dependent Resurvey, Portion of W. Bdy.,
T. 23 S., R. 7 W., Willamette Mer., Oregon

16584

CHAINS

T 23 S	R 7 W
S 19	S 20
S 30	S 29
1979	

FD. 62 1983
BLM SURVEY
Vol. 44 Pg. 172-80

from which

- A fir, 16 ins. diam., bears N. 25° E., 25 lks.
dist., mkd. T23S R7W S20 BT.
- A fir, 16 ins. diam., bears S. 86 1/4° E., 76 lks.
dist., mkd. T23S R7W S29 BT.
- A fir, 14 ins. diam., bears S. 80 3/4° W., 27 lks.
dist., mkd. T23S R7W S30 BT.
- A fir, 10 ins. diam., bears N. 83 1/4° W., 41 lks.
dist., mkd. T23S R7W S19 BT.

From this point, the cor. of secs. 31 and 32 only, on the S. bdy. of the Tp., bears S. 0° 10' E., 160.45 chs. dist., perpetuated and recorded by James W. Byron, County Surveyor, in 1960, monumented with an iron post, 1 in diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

S 31	S 32	T 23 S	R 7 W
		T 24 S	

from which the remains of the original bearing trees

- A white oak, 36 ins. diam., bears S. 10° W., 54 lks.
dist., with healed blaze.
 - A fir, 54 ins. diam., bears N. 13° W., 160 lks.
dist., with healed blaze.
- and the remains of bearing trees mkd. by Byron
- A fir, 14 ins. diam., bears N. 14° E., 20 lks.
dist. with healed blaze.
 - A fir snag, 12 ins. diam., bears N. 57 1/2° W., 58 lks.
dist., with healed blaze.

There are no other suitable trees available.

From this same point, the cor. of secs. 20, 21, 28, and 29 bears S. 89° 00' E., 79.97 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 23 S	R 7 W
S 20	S 21
S 29	S 28
1963	

from which bearing trees mkd. by F. E. Waggoner, Registered Land Surveyor No. 149, in 1955

- A white oak, 28 ins. diam., bears S. 88° E.,
109 lks. dist., with healed blaze.
- A white oak, 24 ins. diam., bears N. 11 1/2° W.,
16 lks. dist., with healed blaze.