

# County Surveyor's Record, Douglas County, Oregon

16585

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 23 S., R. 7 W., Willamette Mer., Oregon

CHAINS	
	<p>and bearing trees mkd. by Brooks and Peterson in 1964</p> <p style="padding-left: 40px;">A double maple, 28 ins. diam., bears N. 85° E., 187 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A white oak, 21 ins. diam., bears S. 65 1/2° W., 88 lks. dist., with healed blaze.</p> <p>These control lines were fully retraced and no evidence of the intervening cors. was found.</p> <p>S. 89° 18' W., bet. secs. 19 and 30, marking and blazing the true line.</p> <p>Descend 40 ft. over NW. slope, through moderate timber and undergrowth.</p>
3.10	Madison Road, asphalt surface, 35 lks. wide, bears N. 75° E. and S. 75° W.
4.20	Wire fence bears N. 75° E. and S. 75° W. Also enter open pasture land.
33.18	<p>Point selected for the witness 1/4 sec. cor. of secs. 19 and 30.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>WC</p> <p>T 23 S R 7 W</p> <p>S 19</p> <p>1/4 ←</p> <p>S 30</p> <p>1979</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 32 ins. diam., bears N 39 1/4° E., 10.14 chs. dist., mkd. X BT.</p> <p style="padding-left: 40px;">An oak, 21 ins. diam., bears S. 4 1/2° W., 10.19 chs. dist., mkd. X BT.</p> <p>The witness cor. is located on top of bank on E. side of Umpqua River.</p> <p>Descend 20 ft. over NW. slope.</p>
35.50	Right bank of Umpqua River, bears N. 30° E., and S. 30° W., course N. 30° E.; thence across river.
38.82	Point for the meander cor. bet. secs. 19 and 30, on the right bank of the Umpqua River, at proportionate distance; there is no remaining evidence of the original corner.
	No permanent monument established.
39.69	True point for the 1/4 sec. cor. of secs. 19 and 30, is located in the Umpqua River where it is impractical to establish a permanent monument.
44.65	Left bank of Umpqua River, bears N. 30° E. and S. 30° W., course N. 30° E.; asc. 780 ft. over SE. slope, enter moderate timber and dense undergrowth, edge bears N. 30° E. and S. 30° W.
46.86	Point for the meander cor. bet. secs. 19 and 30, on the left bank of the Umpqua River, at proportionate distance; there is no remaining evidence of the original corner.