

# County Surveyor's Record, Douglas County, Oregon

16586

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 23 S., R. 7 W., Willamette Mer., Oregon

16586

CHAINS													
	No permanent monument established.												
49.00	Bullock Road, asphalt surface, 35 lks. wide, bears N. 10° E. and S. 10° W.												
52.21	Intersect the W. bdy. of Donation Land Claim No. 45, also wire fence line, extending N. and S.												
70.70	Spur ridge, bears N. 70° E. and S. 70° W.; desc. 5 ft. over NW. slope.												
75.50	Enter open pasture, edge bears generally N. and S.												
79.67	The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.												
	<table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="text-align: center;">T 23 S</td></tr> <tr><td style="text-align: center;">R 8 W</td><td style="text-align: center;">R 7 W</td></tr> <tr><td style="text-align: center;">S 24</td><td style="text-align: center;">S 19</td></tr> <tr><td colspan="2" style="text-align: center;"> </td></tr> <tr><td style="text-align: center;">S 25</td><td style="text-align: center;">S 30</td></tr> <tr><td colspan="2" style="text-align: center;">1964</td></tr> </table>	T 23 S		R 8 W	R 7 W	S 24	S 19			S 25	S 30	1964	
T 23 S													
R 8 W	R 7 W												
S 24	S 19												
S 25	S 30												
1964													
	from which bearing trees mkd. by Brooks and Peterson in 1964												
	A fir, 24 ins. diam., bears N. 6° E., 406 lks. dist., with healed blaze.												
	A fir, 40 ins. diam., bears N. 39° W., 571 lks. dist., with healed blaze.												
	There are no other suitable trees available.												
	From this point, United States Coast and Geodetic Survey triangulation station "KELLOGG," bears S. 11° 48' E., 8.91 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. KELLOGG 1953.												
	Land, E 1/2, river bottom land, W 1/2, hilly. Soil, sandy, clay loam. Timber, fir, cedar, hemlock, alder, maple, oak, and madrone; vine maple, hazel, arrowwood, salmonberry, poison oak, Oregon grape, salal, and fern.												
	From the cor. of secs. 19, 20, 29, and 30.												
	N. 0°50' E., bet. secs. 19 and 20.												
	Descend 40 ft. over NW. slope, through moderate timber and undergrowth.												
1.10	Madison Road, asphalt surface, 35 lks. wide, bears N. 75° E. and S. 75° W.												
1.30	Wire fence, bears N. 75° E. and S. 75° W.; enter cultivated field.												
24.90	Wire fence, bears N. 70° E. and S. 70° W.; enter scattering timber and moderate undergrowth.												
25.05	Top of high bank on S. side of Umpqua River, edge bears N. 70° E. and S. 70° W.; desc. 30 ft. over steep N. slope.												