

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 23 S., R. 7 W., Willamette Mer., Oregon

16588

CHAINS	
	<p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A sawed fir stump, 36 ins. diam., bears S. 27° W., 29 lks. dist., with scribe marks 23S S19 visible on opened blaze.</p> <p>and the remains of the bearing trees mkd. by James W. Byron, County Surveyor, in 1960</p> <p style="padding-left: 40px;">A maple, 24 ins. diam, bears N. 44° E., 37 1/2 lks. dist., with fragmentary scribe marks visible on open blaze.</p> <p style="padding-left: 40px;">A fir snag, 17 ins. diam., bears S. 20° E., 57 lks. dist., with fragmentary scribe marks visible on open blaze.</p> <p style="padding-left: 40px;">A maple, 34 ins. diam., bears S. 66° W., 55 1/2 lks. dist., with fragmentary scribe marks visible on open double blaze.</p> <p style="padding-left: 40px;">A fir snag, 17 ins. diam., bears N. 52° W., 24 1/2 lks. dist., with scribe marks T23S R7W S18 CS BT visible on open double blaze.</p> <p>and bearing trees mkd. by Brooks and Peterson in 1965</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears N. 8° E., 159 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 28 1/4° E., 26 lks. dist. with healed blaze.</p> <p style="padding-left: 40px;">A fir, 27 ins. diam., bears N. 7° W., 118 lks. dist., with healed blaze.</p> <p>Cor. is located on spur ridge, bears N. 10° E. and S. 10° W.</p> <p>Land, S 1/2, river bottom land, N 1/2, hilly. Soil, sandy loam. Timber, fir, hemlock, maple, and oak; undergrowth, Scotch broom, huckleberry, salal, poison oak, and fern.</p>
	<p>S. 89° 48' W., bet. secs. 18 and 19.</p> <p>Descend 80 ft. over NW. slope, through scattering timber and dense undergrowth.</p>
8.70	Bottom of descent, slopes N. 10° W.; asc. 160 ft. over NE. slope.
13.35	Spur, slopes N.; desc. 75 ft. over NW. slope.
16.80	Head of ravine, drains N. 20° W.; asc. 60 ft. over NE. slope.
22.00	Spur, slopes N. 20° W.; desc. 285 ft. over NW. slope.
39.74	Point for the 1/4 sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.