

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Boundaries of
Donation Land Claim No. 45,

16590

T. 23 S., R. 7 W., Willamette Mer., Oregon

CHAINS

in 1938, from original evidence no longer in existence, further perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1966, monumented with an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above ground, alongside of which is an iron pipe, 3/4 ins. diam., firmly set, flush with the surface of the ground from which the remains of bearing trees mkd. by Irving in 1938

An oak, 12 ins. diam., bears S. 82 1/4° E.,
14 lks. dist., with scribe marks DLC 45 CS BT
visible on open blaze.

An oak, 12 ins. diam., bears S. 46° W., 36 lks.
dist., with healed blaze.

and bearing trees mkd. by Tracy in 1966

A fir, 17 ins. diam., bears N. 16 3/4° E., 92 1/2 lks.
dist., with healed blaze.

An oak, 20 ins. diam., bears S. 13 1/2° W., 58 lks.
dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T 23 R 7 W
DLC
45 S 20
 1979

Reset both iron pipes alongside the iron post.

N. 89° 55' W., on the N. bdy. of Donation Land Claim No. 45.

Descend 90 ft. over NW. slope, through moderate timber and undergrowth.

- 6.80 Ravine, drains S. 40° W.; asc. 50 ft. over SE. slope.
- 12.10 Spur, slopes S. 20° W.; desc. 70 ft. over rolling hills.
- 23.20 Gravelled road, 20 lks. wide, bears N. 20° W. and S. 20° E.
- 27.90 Oregon State Highway No. 138, asphalt surface, 40 lks. wide, bears N. 30° W. and S. 30° E.
- 28.80 Wire fence, bears N. 30° W. and S. 30° E.; enter open pasture land.
- 37.00 Enter scattering timber, edge bears generally N. and S.
- 54.33 Intersect the line bet. secs. 19 and 20.
- 59.60 Head of ravine, drains S. 40° E.; asc. 130 ft. over SE. slope.
- 73.50 Spur, slopes S.; desc. 85 ft. over SW. slope.
- 86.40 Head of ravine, drains S. 60° E.; asc. 40 ft. over NE. slope.