



County Surveyor's Record, Douglas County, Oregon

16594

Subdivision of Sec. 19,
T. 23 S., R. 7 W., Willamette Mer., Oregon

CHAINS	
	 from which A fir, 20 ins. diam., bears N. 80 1/2° E., 14 lks. dist., mkd. CN 1/16 S19 BT. A fir, 27 ins. diam., bears N. 71 1/4° W., 40 lks. dist., mkd. CN 1/16 S19 BT. Descend 75 ft. over general N. slope. 69.20 Ravine, drains N. 60° W.; asc. 150 ft. over SW. slope. 80.00 Spur, slopes S. 80° W.; desc. 15 ft. over NW. slope. 80.56 The 1/4 sec. cor. of secs. 18 and 19.
	From the 1/4 sec. cor. of secs. 19 and 20. S. 89° 13' W., on the E. and W. center line of sec.19. Ascend 170 ft. over SE. slope, across open pasture land. 37.15 Spur, slopes S.; desc. 20 ft. over SW. slope. 39.36 Mehl Creek Road, gravelled, 30 lks. wide, bears N. 30° W. and S. 30° E. 39.70 The center 1/4 sec. cor. of sec. 19. Descend 5 ft. over SW. slope. 40.45 Ravine, drains S. 20° E.; asc. 105 ft. over general E. slope. 47.40 Dirt road, 15 lks. wide, bears N. 30° E. and S. 30° W.; also enter scattering timber and undergrowth. 48.65 Spur ridge, bears N. 30° E. and S. 30° W.; desc. 220 ft. over NW. slope. 52.91 Intersect the W. bdy. of Donation Land Claim No. 45; also wire fence extending N. and S.; enter heavy timber and moderate undergrowth. 59.35 Creek, 2 lks. wide, course N.; asc. 10 ft. over E. slope. 59.625 Point for the center W. 1/16 sec. cor. of sec. 19. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  from which A fir, 32 ins. diam., bears S. 80 1/2° E., 67 lks. dist., mkd. CW 1/16 S19 BT.