

County Surveyor's Record, Douglas County, Oregon

16599

16599

T. 33 S., R. 5 W., Willamette, Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines and claim lines, the subdivision of section 21, and the remonumentation of certain original corner points, township 33 south, range 5 west, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey, is as follows:

The north boundary (Seventh Standard Parallel South) and west boundary of the township were surveyed by Butler Ives and George W. Hyde, in 1854.

Mineral Survey Number 141, known as the Dividend Quartz Mine Lode Claim, Mineral Survey Number 142, known as the St. Peters Quartz Mine Lode Claim, and Mineral Survey Number 143, known as the Summit Quartz Mine Lode Claim, were executed by James S. Howard, in 1887.

Mineral Survey Number 197, known as the Division Quartz Lode, was executed by James S. Howard, in 1889.

Mineral Survey Number 233, known as the William Ruble Placer Mining Claim, and Mineral Survey Number 234, known as the Ruth Ruble Placer Mining Claim, were executed by W.F. Briggs, in 1891.

The subdivisional lines of the township were surveyed by Edward F. Sharp, in 1893-94, at which time he established closing corners for the sections to the south on the standard parallel.

In 1901, Oscar F. Thiel surveyed a portion of the subdivisional lines of township 32 south, range 5 west, setting closing corners for certain sections to the north on the standard parallel, thereby causing some of the standard corners to become angle points.

Mineral Survey Number 840, known as the Horseshoe Lode Claim, was executed by Henry M. Lancaster, in 1927.

Certain original corners were remonumented without survey by Joseph S. Gawron, in 1963-64.

Certain original corners were remonumented without survey by Joseph S. Gawron, John M. Jelley, and Rollin D. Aanrud, in 1965-67.

Certain original corners were remonumented without survey by Rollin D. Aanrud, in 1968.

Certain original corners were remonumented without survey by Lynn M. Roseberry and Larry D. Evans, in 1973-74.

The survey was executed in accordance with specifications as set forth in the Manual of Surveying Instructions, 1973, Special Instructions dated June 21, 1977, and Amendment to Special Instructions, dated October 4, 1977, under Group Number 936, Oregon, and the Special Instructions, dated July 13, 1979, under Group Number 1000, Oregon.

The directions of the lines were determined by the solar transit method and by deflections from azimuths obtained by direct solar observations.