

# County Surveyor's Record, Douglas County, Oregon

16601

Dependent Resurvey Portion of Subdivisional Lines,  
T. 33 S., R. 5 W., Willamette Meridian, Oregon

16601

**CHAINS**

A fir, 13 ins. diam., bears S. 35° E., 28 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

A fir, 15 ins. diam., bears S. 22° W., 28 lks. dist., with fragmentary scribe marks visible on partially healed blaze. (Record, S. 23° W., 29 lks.)

A fir, 21 ins. diam., bears N. 30° W., 26 lks. dist., with scribe marks T33S R5W S28 BT visible on partially healed blaze.

North, bet. secs. 27 and 28, marking and blazing the true line.


Ascend 12 ft. over SW slope, through moderate timber and medium undergrowth, across partially logged area.

1.50 Ridge, bears E. and N. 70° W.; desc. 215 ft. over NW. slope.

10.50 Intersect line 1-2 of Dividend Quartz Lode, Mineral Survey No. 141.

Point for the crossing closing cor. of secs. 27 and 28 with line 1-2 of Dividend Quartz Lode.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



from which

A cedar, 8 ins. diam., bears S. 32° E., 91 lks. dist., mkd. T33S R5W S27 CCC BT.


A cedar, 14 ins. diam., bears S. 29° W., 75 lks. dist., mkd. T33S R5W S28 CCC BT.

From this point, cor. No. 2 of Dividend Quartz Lode Mineral Survey No. 141, bears N. 69° 40' E., 4.615 chs. dist., determined at record bearing and distance from the remains of an original bearing tree:

A sawed fir stump, 24 ins. diam., bears West, 20 1/2 lks. dist., with scribe marks BT visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



from which new bearing trees