

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 33 S., R. 5 W., Willamette Meridian, Oregon

16602

**CHAINS**

A fir, 7 ins. diam., bears S. 67 3/4° E., 39 lks. dist., mkd. S27 BT.

A fir, 15 ins. diam., bears N. 68° W., 80 1/2 lks. dist., mkd. MS141 D2 BT.


From this same point, cor. No. 1 of Dividend Quartz Lode, Mineral Survey No. 141, identical with cor. No. 4 of St. Peters Quartz Lode, Mineral Survey No. 142, bears S. 69° 40' W., 17.86 chs. dist., monumented with a mound of stone, 3 ft. base, 6 ins. high, from which the remains of the original bearing trees:

A root hole, bears N. 37 1/2° E., 38 lks. dist., with down and decayed ponderosa pine alongside, 35 ins. diam., with opened and decayed blaze, no marks visible. (Record, N. 42° E., 17 ft.)

A ponderosa pine, 26 ins. diam., bears N. 21 1/4° W., 53 lks. dist., with illegible scribe marks visible on opened blaze. (Record, N. 22° W., 33 ft.)

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.



from which a new bearing tree

A fir, 15 ins. diam., bears N. 6 1/2° E., 157 1/2 lks. dist., mkd. MS141 D1 BT.


Descend 165 ft. over NW. slope.

12.40 Dirt road, 15 lks. wide, bears NE. and SW.

20.04 Intersect line 3-4 of Dividend Quartz Lode, Mineral Survey No. 141.

Point for the crossing closing cor. of secs. 27 and 28 with line 3-4 of Dividend Quartz Lode.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



from which

A cedar, 9 ins. diam., bears N. 51 1/4° E., 53 lks. dist., mkd. T33S R5W S27 CCC BT.

A cedar, 29 ins. diam., bears N. 48 1/4° W., 54 lks. dist., mkd. T33S R5W S28 CCC BT.