

County Surveyor's Record, Douglas County, Oregon

16603

Dependent Resurvey, Portion of Subdivisional Lines,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

16603


CHAINS

From this point, cor. No. 3 of Dividend Quartz Lode, Mineral Survey No. 141, bears N. 69° 43' E., 1.265 chs. dist., determined at record bearing and distance from the remains of an original bearing tree:

A fir snag, 17 ins. diam., bears S. 31° W., 15 lks. dist., with scribe mark 3 visible on partially opened double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



from which new bearing trees

A cedar, 12 ins. diam., bears S. 71° E., 81 lks. dist., mkd. S27 BT.

A fir, 14 ins. diam., bears S. 16 1/2° W., 82 1/2 lks. dist., mkd. MS141 D3 BT.

From this same point, cor. No. 4 of Dividend Quartz Lode, Mineral Survey No. 141, identical with cor. No. 3 of St. Peters Quartz Lode, Mineral Survey No. 142, on line 2-3 of Division Quartz Lode, Mineral Survey No. 197, bears S. 69° 43' W., 21.205 chs. dist., determined at record bearing and distance from the remains of the original bearing tree:


A root hole, bears S. 28° W., 22 1/2 lks. dist., with a down and decayed fir alongside, 14 ins. diam., with illegible scribe marks visible on opened blaze.

and a bearing tree of which I have no record

A fir, 20 ins. diam., bears S. 83° E., 15 lks. dist., with scribe marks 4 S 2 visible on partially opened double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



from which new bearing trees

A cedar, 7 ins. diam., bears S. 66 1/4° E., 25 lks. dist., mkd. MS141 D4 BT.