

County Surveyor's Record, Douglas County, Oregon

16606

Dependent Resurvey, Portion of Subdivisional Lines,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
5.50	Gravelled road, 30 lks. wide, bears NW. and SE.
6.80	Spur, slopes S. 60° W.; continue along W. slope
9.00	Ravine, drains, S. 70° W.; asc. 50 ft. over SE. slope.
11.40	Spur, slopes SW.; asc. 15 ft. along W. slope.
13.33	An original line tree, a black oak, 37 ins. diam., mkd. with 2 notches on N. and S. faces.

	N. 0° 13' E., beginning new measurement.
	Descend 13 ft. along W. slope.
2.65	Ravine, drains SW.; asc. 190 ft. over S. slope.
6.68	Point for the N 1/16 sec. cor. of secs. 21 and 22.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	N 1/16 S 21 S 22 1977
	from which
	A fir, 6 ins. diam., bears S. 35° E., 18 lks. dist., mkd. N 1/16 S22 BT.
	A fir, 22 ins. diam., bears N. 64° W., 69 lks. dist., mkd. N. 1/16 S 21 BT.
	Ascend 50 ft. over S. slope.
8.40	Spur, slopes S. 80° W.; asc. 5 ft. along W. slope.
9.63	An original line tree, a ponderosa pine, 48 ins. diam., mkd. with 2 notches on N. and S. faces.

	N. 0° 13' E., beginning new measurement.
	Ascend 25 ft. along W. slope.
5.00	Spur, slopes W.; desc. 60 ft. over NW. slope.
7.40	Head of ravine, drains N. 80° W.; desc. 80 ft. along W. slope, changing to NW. slope.
14.30	Wet ravine, drains S. 70° W.; asc. 90 ft. over S. slope.
16.93	The cor. of secs. 15, 16, 21, and 22, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.
	T 33 S R 5 W S 16 S 15 S 21 S 22 1968
	from which the original bearing trees
	A live oak, 9 ins. diam., bears N. 35° E., 45 lks. dist., with healed blaze. (Record, 48 lks.)