

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

16610

CHAINS

A fir, 26 ins. diam., bears N. 45 1/2° E., 29 lks. dist., with healed blaze.

A fir, 15 ins. diam., bears S. 80° W., 8 lks. dist., with scribe marks 1/4 S33 visible on partially healed blaze.

N. 88° 45' W., beginning new measurement.

Descend 115 ft. over SW. slope.

3.37 An original line tree, a fir, 55 ins. diam., mkd. with 2 notches on E. and W. faces.

N. 88° 45' W., beginning new measurement.

Descend 385 ft. over SW. slope.

14.95 Ravine, drains SW.; desc. 450 ft. over broken SW. slope, changing to NW. slope.

32.55 Dirt road, 15 lks. wide, bears N. 20° E. and SW.

37.55 Dirt road, 20 lks. wide, bears N. 20° E. and S. 10° W.

37.97 The cor. of secs. 28, 29, 32, and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

T 33 S R 5 W
S 29 | S 28
S 32 | S 33
1966

from which the remains of the original bearing trees

A decayed pine stump, size indeterminate, bears N. 45° E., 40 lks., dist., no mark visible.

A sawed fir stump, 32 ins. diam., bears N. 53 1/4° W., 20 lks. dist., with partially opened blaze, no marks visible. (Record, N. 62° W.)

and the remains of bearing trees mkd. by Gawron, Jelley, and Aanrud

A fir stump, 10 ins. diam., bears N. 33° E., 68 lks. dist., with a down fir alongside, with illegible scribe marks visible on partially healed blaze.

A fir, 15 ins. diam., bears N. 6 1/2° W., 46 lks. dist., with illegible scribe marks visible on partially healed blaze.

and new bearing trees

A fir, 35 ins. diam., bears N. 27 1/2° E., 80 1/2 lks. dist., mkd. T33S R5W S28 BT.

A cedar, 7 ins. diam., bears S. 17° E., 18 1/2 lks. dist., mkd. T33S R5W S33 BT.

A fir, 7 ins. diam., bears S. 48 1/2° W., 60 lks. dist., mkd. T33S R5W S32 BT.