

County Surveyor's Record, Douglas County, Oregon

16611

Dependent Resurvey, Portion of Subdivisional Lines,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

16611

CHAINS	
	<p>Land, mountainous. Soil, rocky clay. Timber, fir, pine, cedar, madrone, and oak; undergrowth, poison oak, hazel, manzanita, and young timber.</p>
	<p>N. 0° 32' E., bet. secs. 28 and 29.</p> <p>Descend 95 ft. over NW. slope, through heavy timber and dense undergrowth, along E. edge of partially logged area.</p>
6.70	Ravine, drains W.; asc. 30 ft. over broken SW. slope.
10.00	Dirt road, 20 lks wide, bears N. 20° E. and S. 20° E., in curve.
13.00	Same dirt road, bears N. 40° W. and S. 30° E., curving S.
16.16	From this point, the NW. corner of a wood frame water tank, 8 x 5 x 5 ft., bears East. 5 lks. dist., long side bears E. and W.
16.40	Spur, slopes NW.; desc. 100 ft. over NW. slope.
20.08	<p>The S 1/16 sec. cor. of secs. 28 and 29, established and recorded by Richard L. Templin, Registered Engineer No. 3024, in 1969, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above ground, from which bearing trees mkd. by Templin:</p> <p style="margin-left: 40px;">A fir, 11 ins. diam., bears N. 31° E., 29 lks. dist., with illegible scribe marks visible on partially healed blaze.</p> <p style="margin-left: 40px;">A cedar, 21 ins. diam., bears N. 49° W., 13 lks. dist., with scribe marks S 1/16 RE3024 BT visible on partially healed blaze.</p> <p>Descend 200 ft. over NW. slope, changing to broken W. slope.</p>
40.14	<p>The 1/4 sec. cor. of secs. 28 and 29, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 16 ins. above ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W 1/4 S 29 S 28 1966</p> <p>from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A ponderosa pine, 18 ins. diam., bears N. 40 3/4° E., 118 lks. dist., with illegible scribe marks visible on open blaze. (Record, N. 40° E.)</p> <p style="margin-left: 40px;">A root crown, bears S. 11° W., 63 lks. dist., with a down and decayed pine alongside, 16 ins. diam., with scribe marks 1/4 visible on burned and decayed blaze.</p> <p>and bearing trees described by Gawron, Jelley, and Aarud</p> <p style="margin-left: 40px;">A ponderosa pine, 15 ins., diam., bears N. 38 1/4° E., 24 lks. dist. with scribe marks RS33 BT visible on partially healed blaze. (Record, N. 44 1/2° E.)</p>