

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

16612

CHAINS

A ponderosa pine, 18 ins. diam., bears N. 85 1/2° W.,
36 lks. dist., with healed blaze. (Record, West)

N. 0° 15' E., beginning new measurement

Descend 20 ft. along W. slope.

1.10 Dirt road, 15 lks. wide, bears N. 20° E. and S 20° W.

4.00 Bottom of descent, slopes W.; asc. 17 ft. along W. slope.

8.09 From this point, the SW. corner of a wood frame shed,
8 x 7 ft. bears East, 16 1/2 lks. dist., long side bears
N. and S.

8.44 Intersect the SW corner of a wood frame dwelling 12 x 8
ft. long side bears N. and S.

9.00 Spur, slopes W.; desc. 110 ft. over N. slope.


9.07 From this point, the NE. corner of a wood frame water
tank, bears East, 3 lks., dist., 8 x 5 x 4 ft., long side
bears N. 70° E. and S. 70° W.

12.50 Ravine, drains NW.; desc. 225 ft. over NW. slope.

20.535 Intersect line 6-7 of Ruth Ruble Placer, Mineral Survey
No. 234.

Point for the crossing closing cor. of secs. 28 and 29
with line 6-7 of Ruth Ruble Placer..

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, with brass cap mkd.



from which

A fir, 17 ins. diam., bears N. 74° E., 40 lks.
dist., mkd. T33S R5W S28 CCC BT.

A fir, 15 ins. diam., bears S. 42° W., 60 lks.
dist., mkd. T33S R5W S29 CCC BT.

Corner is located at top of cut bank of placer mining
tailings area, edge bears E. and W.

From this point, a corner established and recorded by
H.W. Lawrence, Registered Engineer No. 1543, in 1964,
bears S. 2° 52' E., 1.18 chs. dist., monumented with an
iron pipe, 1/2 ins. diam., firmly set, projecting 14 ins.
above ground, with aluminum cap mkd. 1543 RR S29 S28,
from which a bearing tree mkd. by Lawrence:

A maple, 9 ins. diam., bears S. 80° W., 53 lks.
dist., with scribe marks RR S LINE BT 1543
visible on partially healed blaze.