

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

16614

CHAINS	
	From the cor. of secs. 21, 22, 27 and 28.
	S. 89° 50' W., bet. secs. 21 and 28.
	Ascend 20 ft. along N. slope, through medium timber and moderate undergrowth.
3.00	Top of ascent, slope N.; desc. 6 ft. along N. slope, changing to NW. slope.
9.20	An original line tree, a cedar, 35 ins. diam., mkd. with 2 notches on E. and W. faces.

	S. 89° 50' W., beginning new measurement.
	Descend 75 ft. over NW. slope.
2.00	Creek, 10 lks. wide, course N. 10° W.; asc. 225 ft. over NE. slope.
13.30	Spur, slopes NE.; asc. 7 ft. along broken N. slope.
21.80	Spur, slopes NW,; desc. 213 ft. over NW. slope.
30.95	The 1/4 sec. cor. of secs. 21 and 28, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.
	<p>T 33 S R 5 W 1/4 $\frac{S\ 21}{S\ 28}$ 1967</p>
	from which the remaining original bearing tree
	A ponderosa pine, 14 ins. diam., bears S. 75° E., 7 lks. dist., with healed blaze.
	and a bearing tree mkd. by Gawron, Jelley, and Aanrud
	A cedar, 8 ins. diam., bears N. 55° E., 113 lks. dist., with scribe marks 1/4 S21 BT visible on partially healed blaze. (Record, N. 49 1/2° E., 115 lks.)

	N. 89° 25' W., beginning new measurement.
	Descend 45 ft. over W. slope.
1.20	Rocky ravine, drains N. 70° W.; desc. 240 ft. over NW. slope.
10.00	Coyote Creek, 10 lks. wide, course S. 35° W.; asc. 3 ft. over creek bottom.
10.285	Intersect line 8-9 of Ruth Ruble Placer, Mineral Survey No. 234.
	Point for the crossing closing cor. of secs. 21 and 28 with line 8-9 of Ruth Ruble Placer.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.