

County Surveyor's Record, Douglas County, Oregon

16615

Dependent Resurvey, Portion of Subdivisional Lines,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

16615

CHAINS	
	<div style="display: flex; justify-content: center; align-items: center;"> <div style="text-align: center; margin-right: 10px;"> MS 234 RR T 33 S R 5 W 1977 </div> <div style="text-align: center; margin-right: 10px;"> \swarrow S 21 S 28 CCC </div> </div>
	<p>from which</p> <p style="margin-left: 40px;">A cedar, 10 ins. diam., bears N. 88 1/2° E., 99 1/2 lks. dist., mkd. T33S R5W S21 CCC BT.</p> <p style="margin-left: 40px;">A maple, 12 ins. diam., bears S. 10 1/2° E., 95 lks. dist., mkd. T33S R5W S28 CCC BT.</p> <p>From this point, cor. No. 9 of Ruth Ruble Placer, Mineral Survey No. 234, bears N. 57° 28' E., 1.75 chs. dist., hereinafter described.</p> <p>Continue over rocky valley bottom of old placer tailings.</p>
11.00	Leave valley bottom, edge bears NE. and SW.; asc. 20 ft. along S. slope.
14.00	Abandoned mining ditch, 4 lks. wide, bears N. 80° E. and S. 80° W.
16.90	Top of ascent, slopes S.; desc. 20 ft. over SW. slope.
19.10	Ravine, drains S.; asc. 120 ft. over SE. slope.
20.10	Leave placer mining area, edge bears N. and S.; continue across open pasture land.
28.25	Power and telephone line, bears N. 30° E. and S. 30° W.
30.90	Asphalt surfaced road, 30 lks. wide, bears N. 30° E. and S. 30° W.
33.85	Abandoned mining ditch, 10 lks. wide, bears N. 10° W. and S. 40° W., in curve.
37.80	Spur, slopes SE.; desc. 30 ft. over SW. slope.
39.95	Creek, 1 lk. wide, course S. 10° E.; asc. 30 ft. over E. slope.
40.79	The cor. of secs. 20, 21, 28 and 29.
	<p>Land, mountainous with narrow valley bottom. Soil, rocky clay with placer tailing piles in valley. Timber, fir, pine, cedar, oak, madrone, alder, and maple; undergrowth, poison oak, hazel, ceanothus, arrowwood, vine maple, manzanita, wild berry vines, and young timber.</p>
	N. 0° 03' W.; bet. secs. 20 and 21.
	Descend 5 ft. along E. slope, through heavy timber and moderate undergrowth.
1.15	Creek, 1 lk. wide, course S. 30° E.; asc. 440 ft. over S. slope.
19.92	Point for the S 1/16 sec. cor. of secs. 20 and 21.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.