

County Surveyor's Record, Douglas County, Oregon

16617

Dependent Resurvey, Portion of Subdivisional Lines,
T. 33 S., R. 5 W., Willamette Meridian, Oregon.

16617

CHAINS

A black oak snag, 28 ins. diam., bears S. 74° W.,
3 1/2 lks. dist., with scribe marks 1/16 BT
visible on opened and decayed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, with brass cap mkd.

E 1/16 $\frac{S\ 16}{S\ 21}$
1977

from which new bearing trees

A fir, 19 ins. diam., bears N. 88° W., 20 lks.
dist., mkd. E 1/16 S16 BT.

A ponderosa pine, 20 ins. diam., bears S. 41° E.,
17 1/2 lks. dist., mkd. E 1/16 S21 BT.

Deposit point of wood post alongside iron post.

N. 89° 08' W., beginning new measurement.

Ascend 30 ft. over SE. slope.

2.35 Top of ascent, slopes S.; desc. 55 ft. over SW. slope.

6.80 Ravine, drains S. 20° E.; asc. 195 ft. over SE. slope,
changing to S. slope.

20.45 The 1/4 sec. cor. of secs. 16 and 21, monumented with an
iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins.
above ground, with brass cap mkd.

T 33 S R 5 W
1/4 $\frac{S\ 16}{S\ 21}$
1967

from which the remains of the original bearing trees

A black oak snag, 18 ins. diam., bears N. 34° E.,
115 lks. dist., with old axe marks visible on
decayed blaze.

A root hole, bears S. 33 1/4° W., 128 lks. dist., with
a down and decayed black oak alongside, 40 ins.
diam., with old axe marks visible on decayed
blaze.

and bearing trees mkd. by Gawron, Jelley, and Aanrud

A fir, 25 ins., diam., bears N. 12° E., 15 lks.
dist., with healed blaze.

A fir, 18 ins. diam., bears S. 49° W., 15 lks.
dist., with healed blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, pine, cedar, oak, and madrone; undergrowth
poison oak, manzanita, and young timber.