

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

16618

CHAINS

From the 1/4 sec. cor. of secs. 29 and 30, monumented with the original corner tree, a madrone, 10 ins. diam., with healed blaze, from which the original bearing trees:

A fir, 17 ins. diam., bears N. 2° E., 35 lks. dist., with healed blaze.

A fir, 43 ins. diam., bears S. 20° W., 27 lks. dist., with healed blaze.

and a reference monument set by Gawron, Jelley, and Aanrud

An iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, bears N. 45° W., 6 1/2 lks. dist., with brass cap mkd. T33S R5W 1/4 S30 RM 1967 and an arrow pointing to the corner.

N. 0° 08' E., bet. secs. 29 and 30.

Ascend 70 ft. along broken E. slope, changing to SE. slope, through heavy timber and dense undergrowth.

9.60 Spur, slopes S. 60° E.; desc. 40 ft. over NE. slope.

13.00 The remains of an original line tree, burned and decayed double fir snag, 67 ins. diam., mkd. with 2 notches on S. face.

N. 0° 08' E., beginning new measurement.

Descend slightly along E. slope.

0.10 Ravine, drains S. 60° E.; asc. 80 ft. over SE. slope.

3.50 Spur, slopes E.; desc. 250 ft. over NE. slope, changing to N. slope.

10.80 Wet ravine, drains N. 70° E.; asc. 25 ft. over SE. slope.

12.70 Top of ascent, slopes E.; desc. 135 ft. over NE. slope, changing to N. slope.

15.65 Abandoned mining ditch, 4 lks. wide, bears N. 70° W. and S. 70° E.

18.19 Intersect line 5-6 of William Rubble Placer, Mineral Survey No. 233.

Point for the crossing closing cor. of secs. 29 and 30 with line 5-6 of William Ruble Placer.

Set an iron post, 28 ins. long 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

MS 233
WR
S 30 | S 29
T 33 S R 5 W
CCC
1977

from which

A fir, 6 ins. diam., bears S. 13 3/4° E., 57 lks. dist., mkd. T33S R5W S29 CCC BT.