

County Surveyor's Record, Douglas County, Oregon

16619

Dependent Resurvey, Portion of Subdivisional Lines,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

16619

CHAINS

A fir, 8 ins. diam., bears S. 59 3/4° W., 35 lks.
dist., mkd. T33S R5W S30 CCC BT.

From this point, a corner established and recorded by H. W. Lawrence, Registered Engineer No. 1543, in 1964, bears S. 41° E., 0.82 chs. dist., monumented with an iron pipe, 1/2 in. diam., firmly set, projecting 6 ins. above ground, with lead cap mkd. 1543 WRM S29 S30, from which a bearing tree mkd. by Lawrence:

A fir, 10 ins. diam., bears S. 66 1/2° W., 88 1/2 lks.
dist., with healed double blaze.

From this same point, cor. No. 6 of William Ruble Placer, Mineral Survey No. 233, bears S. 88° 30' E., 1.60 chs. dist., hereinafter described.

Descend 30 ft. over N. slope.

19.35 Foot of mountain, edge bears W. and SE.; desc. 10 ft. over bedrock of placer mined area.

21.50 Coyote Creek, 20 lks. wide, course S. 70° W.; asc. 30 ft. over gradual S. slope of placer tailings.

24.60 Leave placer mining area, edge bears N. 60° W. and S. 60° E.; continue over nearly level valley bottom.

24.90 Unimproved dirt road, 15 lks. wide, bears N. 75° E. and S. 75° W.

27.26 The cor. of secs. 19, 20, 29, and 30, located on the W. edge of asphalt surfaced county road, 30 lks. wide, bears N. 30° W. and S. 40° E., perpetuated and recorded by Norman D. Price, Registered Land Surveyor No. 33, in 1954, and further perpetuated by the County Surveyor, in 1971, monumented with an iron post, 1 1/2 ins. diam., firmly set, the top 6 ins. below surface of the road, with brass cap mkd.

COUNTY SURVEYOR
T 33 S R 5 W
19|20
30|29
1971

from which the remaining original bearing trees

A black oak, 25 ins. diam., bears N. 32 1/4° E., 165 lks. dist., with decayed double blaze, no marks visible. (Record, 170 lks.)

and bearing trees mkd. by Price

A fir, 22 ins. diam., bears N. 10° E., 166 lks. dist., with illegible scribe marks visible on partially healed blaze.

A fir, 21 ins. diam., bears S. 28 1/4° E., 316 1/2 lks. dist., with healed blaze.

A fir, 20 ins. diam., bears S. 81° W., 41 lks. dist., with healed blaze.

A fir, 23 ins. diam., bears N. 51 1/4° W., 30 1/2 lks. dist., with healed blaze.