

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisinal Lines,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

16620

CHAINS	
	<p>Land, mountainous except for narrow valley bottom. Soil, rocky clay hillsides with exposed bedrock in valley. Timber, fir, pine, cedar, madrone, oak, chinquapin, alder, and willow; undergrowth, poison oak, hazel, arrowwood, vine maple, manzanita, blackberry, salal, fern, and young timber.</p>
	<p>S. 89° 58' W., bet. secs. 19 and 30.</p> <p>Over nearly level ground, through scattering timber and moderate undergrowth.</p>
0.80	<p>Top of cut bank of placer mining area, edge bears NW. and SE.; desc. 63 ft. over placer tailing.</p>
19.00	<p>Unimproved road, 15 lks. wide, bears N. 55° W. and S. 55° E.</p>
26.00	<p>Coyote Creek, 10 lks. wide, course N. 55° W.; continue over rocky creek bed.</p>
26.22	<p>Intersect line 3-4 of William Ruble Placer, Mineral Survey No. 233.</p> <p>Point for the crossing closing cor. of secs. 19 and 30, with line 3-4 of William Ruble Placer, located in Coyote Creek bed, where it is impracticable to establish a permanent monument.</p> <p>From this point, cor. No. 4 of William Ruble Placer, Mineral Survey No. 233, bears S. 67° 30' E., 7.30 chs. dist., hereinafter described.</p> <p>Ascend, 3 ft. over creek bank.</p>
26.89	<p>Point selected for the witness cor. to the crossing closing cor. of secs. 19 and 30 with line 3-4 of William Ruble Placer.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p style="margin: 0;">W C → MS 233 WR</p> <p style="margin: 0;">CCC S 19 S 30</p> <p style="margin: 0;">T 33 S R 5 W 1977</p> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 6 ins. diam., bears S. 48° W., 46 lks. dist., mkd. X BT.</p> <p style="margin-left: 40px;">A fir, 5 ins. diam., bears N. 86 1/4° W., 21 1/2 lks. dist., mkd. X BT.</p> <p>Continue over valley bottom.</p>
28.00	<p>Foot of mountain, bears N. 70° W. and S. 50° E.; asc. 120 ft. over NE. slope, through heavy timber and dense undergrowth.</p>
33.40	<p>Spur, slopes N.; desc. 30 ft. along N. slope.</p>
36.00	<p>Ravine, drains NE.; asc. 100 ft. over NE. slope.</p>