

County Surveyor's Record, Douglas County, Oregon

16621

Dependent Resurvey, Portion of Subdivisional Lines,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

16621

CHAINS

40.25

The 1/4 sec. cor. of secs. 19 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above solid rock outcropping, with brass cap mkd.

T 33 S R 5 W
1/4 $\frac{S 19}{S 30}$
1967

from which the remains of the original bearing trees

A fir, 9 ins. diam., bears N. 24° E., 7 lks. dist., with healed blaze.

A madrone snag, 8 ins. diam., bears S. 37° W., 7 lks. dist., with scribe marks 1/4 S T visible on partially healed blaze.

and a bearing tree mkd. by Gawron, Jelley, and Aanrud

A fir, 9 ins. diam., bears S. 52 1/2° W., 21 lks. dist., with healed blaze.

S. 89° 02' W., beginning new measurement.

Ascend 55 ft. along steep N. slope.

10.70

Top of ascent, slopes N.; desc. 90 ft. along steep N. slope.

19.92

Point for the W 1/16 sec. cor. of secs. 19 and 30.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 $\frac{S 19}{S 30}$
1977

from which

A fir, 13 ins. diam., bears N. 21 1/4° W., 46 lks. dist., mkd. W 1/16 S19 BT.

A fir, 10 ins. diam., bears S. 67 1/4° W., 36 lks. dist., mkd. W 1/16 S 30 BT.

Descend 180 ft. along N. slope.

33.57

The cor. of secs. 19, 24, 25, and 30, identical with cor. No. 1 of William Ruble Placer, Mineral Survey No. 233, on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 33 S
R 6 W | R 5 W
 $\frac{S 24}{S 25}$ | $\frac{S 19}{S 30}$
1963

from which the remains of a bearing tree mkd. by Sharp

A sawed fir stump, 35 ins. diam., bears S. 81° E., 67 lks. dist., with illegible scribe marks visible on opened blaze.