

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

16622

CHAINS

and the remains of a bearing tree mkd. by H. W. Lawrence, Registered Engineer No. 1543, in 1957

A root hole, bears S. 81° E., 22 lks. dist., with a down fir alongside, 28 ins. diam., with scribe marks W BT visible on double bark blaze.

and bearing trees mkd. by Gawron

A fir, 8 ins. diam., bears N. 37° E., 78 lks. dist., with healed blaze. (Record, N. 43° E.)

A fir, 22 ins. diam., bears S. 53 1/2° E., 60 1/2 lks. dist., with healed blaze.

A fir, 15 ins. diam., bears S. 16 1/4° W., 73 1/2 lks. dist., with healed blaze. (Record, S. 24° W.)

A fir, 14 ins. diam., bears N. 48° W., 69 lks. dist., with healed blaze.

Add marks WR 1 MS 233 1977 to brass cap.

Land, mountainous with placer mined valley east 1/3 mile. Soil, rocky clay hillsides with exposed bedrock in valley. Timber, fir, pine, cedar, madrone, oak, yew, hemlock, chinquapin, alder, and maple; undergrowth, vine maple, poison oak, arrowwood, hazel, manzanita, blackberry, salal, fern, and young timber.

Dependent Resurvey of a Portion of the Claim Lines,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

(Restoring the surveys by W. F. Briggs,
U. S. Deputy Mineral Surveyor, in 1891, and
the survey by Henry M. Lancaster,
U. S. Mineral Surveyor, in 1927)

From cor. No. 1, William Ruble Placer, Mineral Survey No. 233, identical with the cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., hereinbefore described.

N. 75° 00' E., on line 1-2 of William Ruble Placer, Mineral Survey No. 233.

Ascend 7 ft. along N. slope, through heavy timber and dense undergrowth.

22.30 Left bank of Coyote Creek, bears N. 80° W. and S. 80° E.; desc. 8 ft. over creek bank.

22.45 Point for cor. No. 2, William Ruble Placer, Mineral Survey No. 233, determined by the grant boundary method: there is no remaining evidence of the original corner, located in Coyote Creek, 15 lks. wide, course N. 80° W.

Set an iron rod, 24 ins. long, 1/2 in. diam., 18 ins. in the bed of Coyote Creek.

from which

An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 9° 33' W., 16 lks. dist., with brass cap mkd. MS 233WR 2 RM1977 and an arrow pointing to the corner.