

County Surveyor's Record, Douglas County, Oregon

16623

Dependent Resurvey of a Portion of the Claim Lines,
T. 33 S., R. 5 W., Willamette Meridian, Oregon.

16623

CHAINS	
	<p>A fir, 22 ins. diam., bears S. 15° W., 43 lks. dist., mkd. T33S R5W S19 BT.</p> <p>An ash, 10 ins. diam., bears N. 1 1/2° E., 75 lks. dist., mkd. MS 233 WR2 BT.</p>
	<p>S. 83° 00' E., on line 2-3 of William Ruble Placer, Mineral Survey No. 233.</p> <p>Ascend 10 ft. along Coyote Creek.</p>
10.75	<p>Leave Coyote Creek, course W. from NE.; asc. 10 ft. along N. slope, through young timber and moderate undergrowth.</p>
18.96	<p>Point for cor. No. 3, William Ruble Placer, Mineral Survey No. 233, determined by the grant boundary method; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>MS 233 WR 3</p> <p>S 19 1977</p> </div> <p>from which</p> <p>A fir, 7 ins. diam., bears N. 3 1/2° E., 109 lks. dist., mkd. MS 233 WR3 BT.</p> <p>A fir, 10 ins. diam., bears West, 18 1/2 lks. dist., mkd. T33S R5W S19 BT.</p> <p>From this point, a locally established corner of which I have no record, bears S. 17° 16' W., 0.333 chs. dist., monumented with an iron rod, 1/2 in. diam., firmly set, projecting 1 in. above ground.</p>
	<p>S. 67° 30' E., on line 3-4 of William Ruble Placer, Mineral Survey No. 233.</p> <p>Ascend 4 ft. along N. slope, through young timber and moderate undergrowth.</p>
7.665	<p>Intersect the line bet. secs. 19 and 30.</p> <p>The crossing closing cor. of secs. 19 and 30 with line 3-4 of William Ruble Placer, hereinbefore described.</p> <p>From this point, the 1/4 sec. cor. of secs. 19 and 30, bears S. 89° 58' W., 14.03 chs. dist., hereinbefore described.</p> <p>Descend slightly along No. slope.</p>
8.00	<p>Coyote Creek, 12 lks. wide, course N. 55° W.; asc. 20 ft. over SW. slope, through placer tailings.</p>
13.10	<p>Enter gravel pit, edge bears N. 45° W. and S. 55° E.; desc. 10 ft. into pit.</p>
14.965	<p>Point for cor. No. 4, William Ruble Placer, Mineral Survey No. 233, determined by the grant boundary method; there is no remaining evidence of the original corner.</p>