


# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Claim Lines,  
T. 33 S., R. 5 W., Willamette Meridian, Oregon

16624

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



from which

A fir, 10 ins. diam., bears N. 54 1/2° E., 374 lks. dist., mkd. MS 233 WR4 BT.

A fir, 17 ins. diam., bears S. 15 1/2° E., 113 1/2 lks. dist., mkd. T33S R5W S30 BT.

From this point, a locally established corner of which I have no record, bears S. 23° 03' W., 0.465 chs. dist., monumented with an iron rod, 1/2 in. diam., firmly set, projecting 4 ins. above ground.

S. 47° 00' E., on line 4-5 of William Ruble Placer, Mineral Survey No. 233.


Continue across gravel pit.

3.50 Leave gravel pit, edge bears N. 40° E. and N. 60° W.; desc. 4 ft. over S. slope, through placer tailings.

7.90 Coyote Creek, 15 lks. wide, course N. 60° W.; asc. 10 ft. over N. slope.

8.68 Point for cor. No. 5, William Ruble Placer, Mineral Survey No. 233, determined by the grant boundary method; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



from which

A fir, 4 ins. diam., bears S. 3 3/4° E., 25 lks. dist., mkd. X BT.

An alder, 6 ins. diam., bears N. 37 1/2° E., 22 1/2 lks. dist., mkd. MS 233 WR 5.

From this point, a locally established corner of which I have no record, bears S. 27° 15' W., 0.55 chs. dist., monumented with an iron rod, 1/2 in. diam., firmly set, projecting 5 ins. above ground.

S. 88° 30' E., on line 5-6 of William Ruble Placer, Mineral Survey No. 233.

Ascend 35 ft. along steep N. slope, across open slide area.