

County Surveyor's Record, Douglas County, Oregon

16626

Dependent Resurvey of a Portion of the Claim Lines,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

From this point, a corner established and recorded by H. W. Lawrence, Registered Engineer No. 1543, in 1960, bears S. 3° 28' E., 0.61 chs. dist., monumented with a galvanized iron pipe, 3/4 in. diam., firmly set, projecting 12 ins. above ground, with lead cap mkd. WR7 RE 1543, from which a bearing tree mkd. by Lawrence:

A yew, 10 ins. diam., bears S. 48° W., 16 lks. dist., with scribe marks R7 visible on partially healed blaze.

N. 0° 30' W., on line 7-8 of William Ruble Placer, Mineral Survey No 233, identical with line 1-17 of Ruth Ruble Placer, Mineral Survey No. 234.

Descend 10 ft. over N. slope, through young timber and dense undergrowth.

- 0.45 Gravelled road, 15 lks. wide, bears NW. and SE., also foot of mountain, edge bears same as road; desc. 8 ft. over gentle N. slope, through placer tailings.
- 2.35 Coyote Creek, 12 lks. wide, course NW.; asc. 40 ft. over broken SW. slope, through placer tailings.
- 5.70 Dirt road, 15 lks. wide, bears NW. and SE.
- 7.40 Leave placer tailings, enter moderate timber and dense undergrowth, edge bears N. 60° W. and S. 60° E.
- 9.50 Ravine, drains S. 70° W.; asc. 60 ft. over SW. slope.
- 10.70 Asphalt surfaced road, 30 lks. wide, bears N. 65° W. and S. 65° E.
- 12.07 Cor. No. 8, William Ruble Placer, Mineral Survey No. 233, identical with cor. No. 17, Ruth Ruble Placer, Mineral Survey No. 234, perpetuated and recorded by Norman D. Price, Registered Land Surveyor No. 33, in 1954, monumented with an iron pipe, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass washer in top mkd. RS 33, from which the only remaining original bearing tree:

A madrone, 28 ins. diam., bears S. 78 1/2° W., 93 lks. dist., with opened and decayed blaze, no marks visible, and healed blaze at base. (Record, S. 69° W., 87 lks.)

and bearing trees mkd. by Price

A fir, 28 ins. diam., bears S. 9 1/2° E., 64 lks. dist., with healed blaze.

A fir, 20 ins. diam., bears N. 71 1/4° W., 77 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.

