

# County Surveyor's Record, Douglas County, Oregon

16630

Dependent Resurvey of a Portion of the Claim Lines,  
T. 33 S., R. 5 W., Willamette Meridian, Oregon

**CHAINS**

An iron post, 28 ins. long 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 71° E., 10 lks. dist., with brass cap mkd. MS 234 RR8 RM 1977 and an arrow pointing to the corner.

A fir, 8 ins. diam., bears N. 71° W., 33 1/2 lks. dist., mkd. MS 234 RR8 BT.

From this point, a witness cor. established and recorded by R.L. Templin, Jr., Registered Engineer No. 3024, in 1975, bears S. 60° W., 0.03 chs. dist., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above ground, with plastic cap mkd. TEMPLIN RE 3024

N. 57° 28' E., on line 8-9 of Ruth Ruble Placer, Mineral Survey No. 234.

Descend 8 ft. along NW. slope, through young timber and dense undergrowth.

0.80 Foot of mountain, edge bears N. 65° E. and S. 65° W.; desc. 10 ft. over rocky creek bottom.

2.40 Coyote Creek, 10 lks. wide, course W., turning to S. 60° W.; asc. 20 ft. over S. slope, through placer tailings.

5.975 Intersect the line bet. secs. 21 and 28.

The crossing closing cor. of secs. 21 and 28 with line 8-9 of Ruth Ruble Placer, hereinbefore described.

From this point, the 1/4 sec. cor. of secs. 21 and 28, bears S. 89° 25' E., 10.285 chs. dist., hereinbefore described.

Continue over nearly level creek bottom.


6.55 Coyote Creek, 10 lks. wide, course S. 35° W.; asc. 13 ft. along NW. slope.

7.725 Cor. No. 9, Ruth Ruble Placer, Mineral Survey No. 234, determined at record bearing and distance from the remains of an original bearing tree:

A sawed fir stump, 38 ins. diam., bears N. 23 1/2° E., 25 lks. dist., with scribe marks 234 visible on partially opened blaze.

At the corner point

Set an iron post, 28 ins. long 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



from which new bearing trees

A fir, 14 ins. diam., bears N. 58° E., 66 lks. dist., mkd. MS 234 RR9 BT.