

County Surveyor's Record, Douglas County, Oregon

16631

Dependent Resurvey of a Portion of the Claim Lines,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

16631

CHAINS	
	<p style="text-align: center;">A cedar, 15 ins. diam., bears N. 68 1/2° W., 123 lks. dist., mkd. MS 234 RR9 BT.</p> <p>Corner is located at top of placer mining cut bank, edge bears N. 20° E. and S. 35° W.</p>
	<p>N. 37° 34' E., on line 9-10 of Ruth Ruble Placer, Mineral Survey No. 234.</p> <p>Ascend 12 ft. along NW. slope, through young timber and dense undergrowth.</p>
4.50	Top of placer mining cut bank, edge bears NE. and SW.; desc. 10 ft. over NW. slope.
5.70	Coyote Creek, 10 lks. wide, course S. 55° W.; asc. slightly along creek.
6.70	Leave creek, course S. 30° W., from N.; asc. 10 ft. along NW. slope.
8.11	From this point, a corner established and recorded by R. L. Templin Jr. Registered Engineer No. 3024, in 1975 bears N. 51° 36' W., 0.08 chs. dist., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground, with plastic cap mkd. TEMPLIN, RE 3024.
12.50	Coyote Creek, 10 lks. wide, course S. 70° W.; asc. 25 ft. over SE. slope, changing to S. slope.
14.25	Intersect the N. and S. center line of sec. 21. No permanent monument established.
	From this point the center S 1/16 sec. cor. of sec. 21, bears N. 0° 28' W., 8.075 chs. dist., hereinafter described.
15.00	Post Gulch, 5 lks. wide, course S.; asc. 140 ft. over SW. slope.
29.00	Gravelled road, 20 lks. wide, bears N. 30° W. and S. 30° E., curving E.
30.34	Point for cor. No. 10, Ruth Ruble Placer, Mineral Survey No. 234, determined by the broken boundary method; there is no remaining evidence of the original corner. No permanent monument established.
	<p>N. 44° 16' W., on line 10-11 of Ruth Ruble Placer, Mineral Survey No. 234.</p> <p>Descend 30 ft. over SW. slope, through young timber and dense undergrowth.</p>
2.875	Point for cor. No. 11, Ruth Ruble Placer, Mineral Survey No. 234, determined by the broken boundary method; there is no remaining evidence of the original corner. No permanent monument established.
	This point is located in asphalt surfaced road, 20 lks. wide, bears N. 30° W. and S. 30° E.
	<p>N. 66° 00' W., on line 11-12 of Ruth Ruble Placer, Mineral Survey No. 234.</p>