


County Surveyor's Record, Douglas County, Oregon

16632

Dependent Resurvey of a Portion of the Claim Lines,
T. 33 S., R. 5 W., Willamette Meridian, Oregon.

CHAINS	
2.685	<p>Descend 15 ft. over SW. slope, through young timber and dense undergrowth.</p> <p>Point for cor. No. 12, Ruth Ruble Placer, Mineral Survey No. 234, determined by the broken boundary method; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>S 21</p>  </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 18 ins. diam., bears S. 23° W., 198 lks. dist., mkd. MS 234 RR12 BT.</p> <p style="margin-left: 40px;">A cedar, 24 ins. diam., bears N. 68 1/4° E., 62 lks. dist., mkd. MS 234 RR12 BT.</p> <p>Corner is located in road fill, above Post Gulch (over metal culvert), 5 lks. wide, course S. 50° W.</p>
0.25	<p>S. 54° 39' W., on line 12-13 of Ruth Ruble Placer, Mineral Survey No. 234.</p> <p>Over broken S. slope, through placer tailings.</p> <p>Asphalt surfaced road, 30 lks. wide, bears N. 70° W., curving SW., and S. 25° E.</p>
2.60	<p>Top of placer mining cut bank, edge bears N. 10° W. and S. 20° W.; desc. 5 ft. over SE. slope, through young timber and dense undergrowth.</p>
6.72	<p>Intersect the N. and S. center line of sec. 21.</p> <p>Point for the crossing closing cor. on the N. and S. center line of sec. 21 with line 12-13 of Ruth Ruble Placer, hereinafter described.</p> <p>From this point, the center S 1/16 sec. cor. of sec. 21, bears S. 0° 16' E., 4.27 chs. dist., hereinafter described.</p> <p>Descend 5 ft. over SE. slope.</p>
13.70	<p>Power and telephone lines, bears N. 80° E. and S. 80° W.</p>
14.03	<p>Intersect the E. and W. center line of the SW 1/4 of sec. 21.</p> <p>Point for the crossing closing cor. on the E. and W. center line of the SW 1/4 of sec. 21 with line 12-13 of Ruth Ruble Placer, hereinafter described.</p> <p>From this point, the center S 1/16 sec. cor. of sec. 21, bears S. 89° 36' E., 5.98 chs. dist., hereinafter described.</p>
16.10	<p>Asphalt surfaced road, 30 lks. wide, bears N. 80° E. and S. 60° W., in curve.</p>