


County Surveyor's Record, Douglas County, Oregon

16633

Dependent Resurvey of a Portion of the Claim Lines,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

16633

CHAINS	
	Descend slightly along broken SE. slope.
24.00	Creek, 1 lk. wide, course SE.; asc. 20 ft. over E. slope.
25.00	Asphalt surfaced road, 30 lks. wide, bears N. 30° E. and S., curving SW.
26.00	Top of ascent, slopes SE.; desc. 50 ft. along S. slope.
29.00	Power and telephone lines, bears NE. and SW.
38.95	<p>Cor. No. 13, Ruth Ruble Placer, Mineral Survey No. 234, determined at record bearing and distance from the remains of an original bearing tree:</p> <p style="padding-left: 40px;">A decayed black oak root crown, 30 ins. diam., bears N. 73° E., 37 lks. dist., with a down and decayed black oak alongside, size indeterminate, with old axe marks visible on pieces of decayed blaze and overgrowth.</p> <p>This position is substantiated by a tie to an originally recorded item of topography, an abandoned mining ditch, 10 lks. wide, extending E. and W., turning SW., bears S. 42° W., 1.64 chs. dist.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>S 21</p>  </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 25 1/4° W., 40 lks. dist., mkd. MS 234 RR13 BT.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 29° W., 41 lks. dist., mkd. MS 234 RR13 BT.</p> <p>Corner is located at end of old fence line, extending S. 42° W.</p>
4.985	<p>From cor. No. 3 Horseshoe Lode, Mineral Survey No. 840, identical with cor. No. 7, Ruth Ruble Placer, Mineral Survey No. 234, hereinbefore described.</p> <p>N. 63° 27' E., on line 3-4 of Horseshoe Lode, Mineral Survey No. 840.</p> <p>Ascend 6 ft. along gentle NW. slope, through young timber and moderate undergrowth.</p> <p>Cor. No. 4, Horseshoe Lode, Mineral Survey No. 840, perpetuated and recorded by R. L. Templin, Jr., Registered Engineer No. 3024, in 1975; monumented with an iron rod 5/8 in. diam., firmly set, projecting 3 ins. above ground, in a mound of stone, 3 ft. base, 1 ft. high, with plastic cap mkd. TEMPLIN RE 3024, from which the remains of the original bearing trees:</p>