

# County Surveyor's Record, Douglas County, Oregon

16634

Dependent Resurvey of a Portion of the Claim Lines,  
T. 33 W., R. 5 W., Willamette Meridian, Oregon


CHAINS

A sawed fir stump, 32 ins. diam., bears S. 19 1/4° E., 65 lks. dist., with scribe marks X H4 840 BT. visible on bark blaze. (Record, S. 20° 48' E., 41.99 ft.)

A sawed fir stump, 46 ins. diam., bears S. 29 1/4° W., 83 1/2 lks. dist., with scribe marks X BT H4 840 visible on bark blaze. (record, S. 28° 55' W.,) 45.11 ft.)

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over iron rod, in a mound of stone, 3 ft. base, to top, with brass cap mkd.



from which new bearing trees

A fir, 15 ins. diam., bears S. 12 1/2° E., 95 lks. dist., mkd. MS 840 H4 BT.

A cedar, 14 ins. diam., bears S. 8 3/4° W., 90 lks. dist., mkd. MS 840 H4 BT.

S. 34° 21' E., on line 4-5 of Horseshoe Lode, Mineral Survey No. 840.

Ascend 285 ft. over N. slope, through medium timber and moderate undergrowth.

8.42


Cor. No. 5, Horseshoe Lode, Mineral Survey No. 840, monumented with a mound of stone, 4 ft. base, 1 ft. high, from which the original bearing trees:

A cedar, 12 ins. diam., bears S. 81° 50' E., 10 1/2 lks. dist., with healed blaze.

A cedar, 8 ins. diam., bears S. 10 1/4° W., 5 1/2 lks. dist., with scribe marks H5 840 BT visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.



from which a new bearing tree

A ponderosa pine, 25 ins. diam., bears N. 51 3/4° W., 85 1/2 lks. dist., mkd. MS 840 H5 BT.

S. 55° 37' W., on line 5-1 of Horseshoe Lode, Mineral Survey No. 840.