

County Surveyor's Record, Douglas County, Oregon

16637

Subdivision of Section 21, T. 33 S., R. R W.,
Willamette Meridian, Oregon

16637

CHAINS


19.00 Leave dry pond area, edge bears N. 70° E., and S. 70° W.; asc. 15 ft. over SE. slope of placer mining cut bank.

20.085 The center S 1/16sec. cor. of sec. 21, established and recorded by Horace C. Hall, County Surveyor, in 1915, and is accepted as the corner, monumented with the point of a decayed wood post, firmly set flush with surface of the ground, from which a bearing tree mkd. by Hall:

A broken topped black oak, 30 ins. diam., bears N. 27° W., 87 1/2 lks. dist., with illegible scribe marks visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



from which new bearing trees

A cedar, 14 ins. diam., bears N. 61° E., 9 lks. dist., mkd. CS 1/16 S21 BT.

A ponderosa pine, 14 ins. diam., bears S. 3° W., 26 lks. dist., mkd. CS 1/16 S21 BT.

Deposit point of decayed wood post alongside iron post.

N. 0° 16' W., beginning new measurement.


Ascend 12 ft. over SE. slope of placer mining cut bank.

0.50 Top of placer mining cut bank, edge bears NE. and SW.; asc. 17 ft. over SE. slope.

4.27 Intersect line 12-13 of Ruth Ruble Placer, Mineral Survey No. 234

Point for the crossing closing cor. on the N. and S. center line of sec. 21 with line 12-13 of Ruth Ruble Placer.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



from which

A ponderosa pine, 14 ins. diam., bears N. 22 1/2° E., 123 lks. dist., mkd. S21 CCC BT.

A cedar, 9 ins. diam., bears N. 40° W., 121 lks. dist., mkd. S21 CCC BT.