

County Surveyor's Record, Douglas County, Oregon

16638

Subdivision of Section 21, T. 33 S., R. 5 W.,
Willamette Meridian, Oregon

CHAINS	
	<p>From this point, cor. No. 12, Ruth Ruble Placer, Mineral Survey No. 234, bears N. 54° 39' E., 6.72 chs. dist., hereinbefore described.</p> <p>Ascend 60 ft. over SE. slope.</p>
4.60	<p>Asphalt surfaced road, 30 lks. wide, bears N. 60° E. and S. 60° W.</p>
9.90	<p>Ravine, drains S. 20° E.; asc. 70 ft. over SW. slope.</p>
12.40	<p>Gravelled road, 20 lks. wide, bears N. 60° E. and W., in curve.</p>
14.00	<p>Spur, slopes S. 10° E.; asc. 100 ft. over SE. slope.</p>
20.075	<p>The center 1/4 sec. cor. of sec. 21, at intersection with the E. and W. center line, established and recorded by Horace C. Hall, County Surveyor, in 1915, and is accepted as the corner, monumented with the point of a decayed wood post, firmly set flush with surface of the ground, from which bearing trees mkd. by Hall:</p> <p style="padding-left: 40px;">A black oak, 28 ins. diam., bears S. 17 1/4° E., 25 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A black oak, 25 ins. diam., bears N. 12° W., 34 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C 1/4 S 21 1977</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 18° E., 25 1/2 lks. dist., mkd. C. 1/4 S21 BT.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 44° W., 11 lks. dist., mkd. C. 1/4 S21 BT.</p> <p style="padding-left: 40px;">Deposit point of wood post alongside iron post.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p>N. 0° 21' W., beginning new measurement.</p> <p>Ascend 145 ft. over SE. slope.</p>
11.70	<p>Spring seepage, drains S. 30° E.; asc. 15 ft. over SE. slope.</p>
13.00	<p>Spring seepage, drains S. 60° E.; asc. 150 ft. over SE. slope.</p>
20.14	<p>Point for the center N 1/16 sec. cor. of sec. 21.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 S 21 C 1977</p>