

# County Surveyor's Record, Douglas County, Oregon

16641

Subdivision of Section 21, T. 33 S., R 5 W.,  
Willamette Meridian, Oregon

16641

CHAINS	
	Descend 420 ft. over broken SW. slope, through medium timber and dense undergrowth.
20.395	The NE 1/16 sec. cor. of sec. 21.  Descend 50 ft. over W. slope.
23.00	Post Gulch, 2 lks. wide, course S. 10° W.; asc. 3 ft. over SE. slope.
27.00	Enter spring seepage, drains S.; asc. 7 ft. over SE. slope.
28.70	Leave spring seepage; asc. 250 ft. over E. slope, changing to SE. slope.
40.73	The center N 1/16 sec. cor. of sec. 21.
	From the center S 1/16 sec. cor. of sec. 21.  N. 89° 36' W., on the E. and W. center line of the SW 1/4 of sec. 21.  Ascend 12 ft. over SE. slope of placer mining cut bank.
0.25	Top of placer mining cut bank, edge bears N. 20° E. and S. 20° W.; asc. 25 ft. over SE. slope, through medium timber and moderate undergrowth, across partially logged area.
2.80	Power and telephone lines, bears N. 10° W. and S. 10° E.
5.98	Intersect line 12-13 of Ruth Ruble Placer, Mineral Survey No. 234.  Point for the crossing closing cor. on the E. and W. center line of the SW 1/4 of sec. 21 with line 12-13 of Ruth Ruble Placer, located in asphalt surfaced road, 30 lks. wide, bears N. 30° E. and S. 30° W., curving SW.  Set an iron post, 18 ins. long, 1 in. diam., 24 ins. in the ground, the top 6 ins. below surface of road, with brass cap mkd.
	from which  A fir, 8 ins. diam., bears S. 69 1/4° W., 88 lks. dist., mkd. S21 CCC BT.  A ponderosa pine, 21 ins. diam., bears N. 28 1/4° W., 72 1/2 lks. dist., mkd. S21 CCC BT.
	From this point, cor. No. 13, Ruth Ruble Placer, Mineral Survey No. 234, bears S. 54° 39' W., 24.92 chs. dist., hereinbefore described.
	Ascend 20 ft. over SE. slope.