

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 21, T. 33 S., R. 5 W.,
Willamette Meridian, Oregon

16642

CHAINS

- 7.10 Spur, slopes S.; also power and telephone line, bears N. 80° E. and S. 80° W.; asc. 80 ft. along broken S. slope.
- 15.40 Top of ascent, slopes S.; desc. 40 ft. over SW. slope.
- 20.15 Creek 1 lk. wide, course SE.; asc. 230 ft. over E. slope.
- 30.80 Spur, slopes S. 20° E.; desc. 25 ft. over SW. slope.
- 35.30 Ravine, drains S. 20° E.; asc. 150 ft. over SE. slope.
- 40.61 The S 1/16 sec. cor. of secs. 20 and 21.

Remonumentation of Certain Original Corner Points,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

The following field notes describe the remonumentation of certain original corner points, township 33 south, range 5 west, Willamette Meridian, Oregon, as provided for in the Special Instructions, Group Number 1000, Oregon, dated July 13, 1979, "Investigation of Physical Evidence of Corner Positions and Accessories, Followed by Remonumentation of Corner Points, with New Accessories when Needed."

The remonumentation of original corner points was made at the request of the District Manager, Medford, for administrative purposes of the Bureau of Land Management.

North Boundary, T. 33 S., R. 5 W.,
(Seventh Standard Parallel South)
Willamette Meridian, Oregon

(Remonumenting corners established by Butler Ives and George W. Hyde, U. S. Deputy Surveyor's in 1854, changed to corners of minimum control by Edward F. Sharp, U. S. Deputy Surveyor in 1893-94, and changed to angle points by Oscar F. Thiel, U. S. Deputy Surveyor in 1901)

The Ives and Hyde standard 1/4 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp., determined at record bearing and distance from the only remaining original bearing tree:

A madrone, 22 ins. diam., bears N. 37° E., 50 lks. dist., with scribe marks 1/4 visible on open and decayed blaze.

This corner now becomes angle point No. 1 of secs. 4 and 33.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, 2 ft. base, to top, with brass cap mkd.