

County Surveyor's Record, Douglas County, Oregon

16643

Remonumentation of Certain Original Corner Points,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

16643

CHAINS

AP 1
T 32 S R 5 W
S 33
S 4
T 33 S
1980

from which new bearing trees

A fir, 13 ins. diam., bears N. 84 1/2° E., 122 1/2 lks.
dist., mkd. AP1 S33 BT.

A fir, 15 ins. diam., bears S. 17 1/2° W.; 125 lks.
dist., mkd. AP1 S4 BT.

The Ives and Hyde standard cor. of secs. 4, 5, 32, and 33,
on the N. bdy. of the Tp., determined at record bearing
and distance from the remains of a bearing tree mkd. by
Thiel:

A fir snag, 80 ins. diam., bears S. 51° W., 72 lks.
dist., with scribe marks T33S R5W S5 B visible
on opened blaze.

This corner now becomes angle point No. 2 of secs. 4 and
33.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins.
in the ground, in a mound of stone, 3 ft. base, to top,
with brass cap mkd.

AP 2
T 32 S R 5 W
S 33
S 4
T 33 S
1980

from which new bearing trees

A white fir, 14 ins. diam., bears N. 25 1/4° W., 27
lks. dist., mkd. AP2 S33 BT.

A hemlock, 14 ins. diam., bears S. 11 1/2° W., 100 1/2
lks. dist., mkd. AP2 S4 BT.

Corner is located 20 lks. east of Woodford Creek, 5 lks.
wide, course N.

East Boundary, T. 33 S., R. 5 W.,
Willamette Meridian, Oregon

(Remonumenting a corner established by Edward F. Sharp,
U. S. Deputy Surveyor, in 1893-94)

The 1/4 sec. cor. of secs. 7 and 12, on the E. bdy of the
Tp., monumented with the original basalt stone, 18 x 12 x
10 ins. firmly set 12 ins. in the ground, mkd. 1/4 on W.
face, from which the remains of the original bearing trees: