

County Surveyor's Record, Douglas County, Oregon

16648

Dependent Resurvey, Portion of S. Bdy.,
T. 24 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 24 S 7 W
S 33
S 4 | S 3
T 25 S
1973

from which the remains of an original bearing tree

A burned fir snag, 25 ins. diam., bears N. 43° E., 22 lks. dist., with fragmentary scribe marks visible on open blaze.

and the remains of a bearing tree mkd. by Zirpel in 1958

A sawed cedar stump, 28 ins. diam., bears S. 31° W., 32 1/2 lks. dist., with fragmentary scribe marks visible on open blaze.

and bearing trees mkd. by Berry and Akin

A fir, 10 ins. diam., bears S. 12 1/2° E., 31 1/2 lks. dist., with healed blaze.

A fir, 12 ins. diam., bears S. 81° W., 61 1/2 lks. dist., with healed blaze.

From this point, the closing cor. of secs. 33 and 34, T. 24 S., R. 7 W., bears N. 89° 32' E., 3.10 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

CC
T 24 S R 7 W
S 33 | S 34
S 3
T 25 S R 7 W
1973

from which bearing trees mkd. by Berry and Atkin

A fir, 14 ins. diam., bears N. 37° E., 192 1/2 lks. dist., with healed blaze.

A fir, 11 ins. diam., bears N. 43 1/2° W., 126 1/2 lks. dist., with healed blaze.

S. 89° 59' W., bet. secs. 4 and 33, marking and blazing the true line.

Descend 360 ft. over SW. slope.

11.15 Creek, 4 lks. wide, course N.; asc. 165 ft. over NE. slope.

17.80 Ridge, bears N. and S.; desc. 130 ft. over W. slope.

26.30 Creek, 2 lks. wide, course N.; asc. 50 ft. over NE. slope.

32.30 Ridge, bears N. and S.; desc. 105 ft. over NW. slope, also dirt road, 10 lks. wide, bears N. and S.