

# County Surveyor's Record, Douglas County, Oregon

16649

16649

Dependent Resurvey, Portion of S. bdy.,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
36.97	<p>Point for the 1/4 sec. cor. of sec. 33 only, T. 24 S., R. 7 W., hereinafter described.</p> <p>Descend 65 ft. over NW. slope.</p>
40.20	<p>The 1/4 sec. cor. of sec. 4 only, T. 25 S., R. 7 W., perpetuated and recorded by Bert Udell, Registered Logging Engineer No. 2301, in 1948, from original evidence no longer in existence, and further perpetuated and recorded by Vernon Tracy, County Surveyor in 1966, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 24 S</p> <p>1/4 ——— R</p> <p style="margin-left: 100px;">S 4 7</p> <p>T 25 S W</p> <p>1966</p> </div> <p>from which the remains of bearing trees mkd. by Udell</p> <p style="margin-left: 40px;">A root hole, bears N. 52° E., 46 lks. dist., with a down fir alongside, 34 ins. diam., with axe marks visible on decayed blaze.</p> <p>and bearing trees mkd. by Tracy</p> <p style="margin-left: 40px;">A fir, 18 ins. diam., bears N. 8° E., 98 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A fir, 16 ins. diam., bears S. 63° E., 140 lks. dist., with healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 56' W., beginning new measurement.</p> <p>Descend 465 ft. over NW. slope.</p>
21.05	Gravelled road, 25 lks. wide, bears N. 20° W. and S. 20° E.
24.75	Creek, 5 lks. wide, course N. 10° W.; asc. 265 ft. over NE. slope.
27.95	Gravelled road, 25 lks. wide, bears N. 20° W. and S. 20° E.
31.60	Spur. slopes N.; desc. 5 ft. over NW. slope.
32.30	Ravine, drains N.; asc. 15 ft. over NE. slope.
36.84	<p>The closing cor. of secs. 32 and 33, hereinafter described.</p> <p>Ascend slightly over NE. slope.</p>
37.63	<p>The cor. of secs. 4 and 5 only, T. 25 S., R. 7 W., perpetuated and recorded by Milo Godfrey, Deputy County Surveyor in 1962, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>R 7 W</p> <p>S 5   S 4</p> <p>T 25 S</p> <p>1962</p> </div> <p>from which the remains of the original bearing trees</p>