

County Surveyor's Record, Douglas County, Oregon

16650

Dependent Resurvey, Portion of S. Bdy.,
T. 24 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A fir, 73 ins. diam., bears N. 37° E., 113 lks. dist., with healed blaze.

A sawed fir stump, 56 ins. diam., bears S. 48° E., 135 lks. dist., no marks remain.

A decayed fir stump, size indeterminate, bears S. 60° W., 29 lks. dist., no marks remain.

A madrone stump, size indeterminate, bears N. 35° W., 63 lks. dist., no marks remain.

and bearing trees mkd. by Godfrey

A fir, 45 ins. diam., bears S. 12° E., 22 lks. dist., with healed blaze.

A fir, 25 ins. diam., bears S. 17° W., 22 lks. dist., with healed blaze.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, maple, oak, madrone, alder, and chinquapin; undergrowth, salal, Oregon grape, poison oak, rhododendron, vine maple, and fern.

Dependent Resurvey of
a Portion of the Subdivisional Lines,
T. 24 S., R. 7 W., Willamette Meridian, Oregon

(Restoring the survey by Dennis Hathorn, U.S. Deputy Surveyor in 1858, and the survey by Williams R. Whipple, U.S. Deputy Surveyor, in 1893-94)

From the cor. of secs. 28, 29, 32 and 33, perpetuated and recorded by H. L. Eppstein, County Surveyor, in 1926, further perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1960, and by Bruce Shaner, Registered Engineer No. 4906, in 1972, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 12 ins. above the ground with brass cap mkd.

COUNTY SURVEYOR'S OFFICE

T 24 S	R 7 W
S 29	S 28
S 32	S 33
1960	

from which the remains of an original bearing tree

An oak, 36 ins. diam., bears N. 1° W., 255 lks. dist., with axe marks visible on open and decayed blaze. (Record, N. 3° E.)

and bearing trees mkd. by Eppstein

An oak, 24 ins. diam., bear N. 59° E. 82 lks. dist., with healed blaze.

An oak, 20 ins. diam., bears S. 67 1/2° E., 97 lks. dist., with healed blaze.

An oak, 19 ins. diam., bears N. 81° W., 35 1/2 lks. dist., with healed blaze.