

County Surveyor's Record, Douglas County, Oregon

16651

16651

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

and a bearing tree mkd. by Shaner

A fir, 15 ins. diam., bears S. 62° W., 25 lks.
dist., with healed blaze.

S. 0° 29' W., bet. secs. 32 and 33, marking and blazing
the true line.

Descend 210 ft. over S.E. slope, through scattering timber
and dense undergrowth.

19.85 Left bank of the Umpqua River, bears N. 80° W., and
S. 80° E.; course S. 80° E.; desc. slightly in river
bottom, over sandstone bedrock, exposed during periods of
low water.

19.91 The original meander cor. of secs. 32 and 33, on the left
bank of the Umpqua River, determined from the remains of
an original bearing tree

A root hole, bears N. 2° W., 334 lks. dist., with
a down oak alongside, 22 ins. diam., with scribe
marks S32 visible on open blaze.

At the corner point

Seat a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in drill
hole in bedrock, with top mkd.

T 24 S		R 7 W
S 32		S 33
M C		
1979		

FDOK
Mark Smalley
9/96 M124-27

from which new bearing trees

A triple cedar, 23 ins. diam., bears N. 3 1/2° E.,
266 lks. dist., mkd. T24S R7W S33 MC BT.

A cedar, 25 ins. diam., bears N. 15° W., 271 lks.
dist., mkd. T24S R7W S32 MC BT.

From this point, a cor. established by James W. Byron
Deputy County Surveyor, in 1960, bears North, 3.33 chs.
dist., monumented with an iron post, 1 1/2 ins. diam.,
firmly set, projecting 16 ins. above ground, with brass
cap mkd. WIT COR. T24S R7W S32 S33 220 to MC 1960, from
which bearing trees mkd. by Byron

An oak, 18 ins. diam., bears N. 76° E., 42 lks.
dist., with healed blaze.

A fir, 18 ins. diam., bears S. 71 1/2° W., 50 lks.
dist., with healed blaze.

S. 0° 58' W., beginning new measurement.

Descend slightly to river bottom, over sandstone bedrock,
exposed during periods of low water.

0.25 Point for the N. 1/16 sec. cor. of secs. 32 and 33.

Seat a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in drill
hole in bedrock, with top mkd.