


County Surveyor's Record, Douglas County, Oregon

16652

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., T. 7 W., Willamette Meridian, Oregon

CHAINS



from which

A fir, 17 ins. diam., bears N. 7 1/2° E., 321 lks. dist., mkd. N 1/16 S33 BT.

A fir, 28 ins. diam., bears N. 3 1/2° W., 265 lks. dist., mkd. N 1/16 S32 BT.


Cor. is located at waters edge, bears N. 80° W. and S. 80° E., course S. 80° E.

Thence across the Umpqua River.

7.53

Point for the meadner cor. of secs. 32 and 33, on the right bank of the Umpqua River, at proportionate distance; there is no remaining evidence of the original cor. This point is located at waters edge, bears E. and W.; course E.

Seat a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in drill hole in bedrock, with top mkd.



from which

An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 15° E., 25 lks. dist., with brass cap mkd. T24S R7W S33 MC RM 1979 and an arrow pointing to the cor.

A myrtle, 16 ins. diam., bears S. 22 1/2° W., 41 lks. dist., mkd. T24S R7W S32 MC BT.

Ascend 190 ft. over NE. slope.

8.21

From this point, a local cor. established by person(s) unknown, bears East, 0.016 chs. dist., monumented with a fir stake, 4 x 1 ins., firmly set, projecting 12 ins. above ground, from which a local bearing tree of which I have no record

A myrtle, 12 ins. diam., bears N. 25° E., 16 lks. dist., with fragmentary scribe marks visible on open blaze.

9.50

Gravelled road, 30 lks. wide, bears E. and W.

12.90

Spur, slopes N. 15° W.; asc. 135 ft. over broken NW. slope.

17.00

Spur, slopes N. 50° W.; asc. 30 ft. over broken NW. slope.

20.32

The 1/4 sec. cor. of secs. 32 and 33, perpetuated and recorded by Milo Godfrey, Deputy County Surveyor, in 1962, monumented with an iron post, 1 1/4 ins. diam., firmly