

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 7 W., Willamette Mer., Oregon

16654

CHAINS

from which the original bearing trees

A fir, 30 ins. diam., bears N. 86° E., 19 lks.
dist., with healed blaze.

A fir, 48 ins. diam., bears N. 35 1/2° W., 25 lks.
dist., with healed blaze.

and a bearing tree mkd. by Godfrey

A fir, 11 ins. diam., bears N. 65 1/2° W., 51. lks.
dist., with healed blaze.

From this point the cor. of secs. 4 and 5 only, T. 25 S.,
R. 7 W., bears N. 89° 56' W., 0.79 chs. dist., hereinbefore
described.

Land, mountainous.
Soil, rocky clay loam.
Timber, fir, hemlock, cedar, maple, oak, alder, madrone,
and chinquapin; undergrowth, salal, poison oak, Oregon
grape, vine maple, and ferns.

To complete the survey of sec. 33, return to the 1/4 sec.
cor. of sec. 4 only, on the N. bdy. of T. 25 S., R. 7 W.,
and run

N. 89° 59' E., on the S. bdy. of sec. 33.

3.23

Point for the 1/4 sec. cor. of sec. 33 only, at midpoint in
departure on the S. bdy. of sec. 33.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in
the ground, with brass cap mkd.

T 24 S R 7 W
1/4 S 33

T 25 S R 7 W
1979

from which

A fir, 16 ins. diam., bears N. 10° E., 29 1/2 lks.
dist., mkd. 1/4 S33 BT.

A fir, 22 ins. diam., bears N. 30° W., 12 1/2 lks.
dist. mkd. 1/4 S33 BT.

Meanders of the Umpqua River

From the meander cor. of secs. 32 and 33, on the right
bank of the Umpqua River, hereinbefore described; thence
downstream with the adjusted meanders of the right bank
of the river in sec. 33.

N. 57° 32' E., 3.73 chs. End of course.

N. 56° 32' E., 9.54 chs. True point for the special
meander cor. on the E. and W.
center line of the NW 1/4 of
sec. 33, hereinafter described.

13.79 chs. End of course.