

County Surveyor's Record, Douglas County, Oregon

16655

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 7 W., Willamette Mer., Oregon

16655

CHAINS											
	<p>N. 24° 40' E., 18.40 chs. Leave river, edge bears N. 15° E. and S. 15° W.; asc. slightly along river bank.</p> <p style="text-align: center;">19.57 chs. At end of this course, the meander cor. of secs. 28 and 33, monumented with a brass tablet, 3 1/2 ins. diam., firmly set, 4 ins. below surface of oiled road, 20 lks. wide, bears N. 15° E. and S. 15° W., with top mkd.</p> <div style="text-align: center; margin-left: 100px;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td></td><td>T 24 S</td></tr> <tr><td>MC</td><td>S 28</td></tr> <tr><td></td><td style="border-top: 1px solid black;">S 33</td></tr> <tr><td></td><td>R 7 W</td></tr> <tr><td></td><td>1973</td></tr> </table> </div> <p>from which bearing trees mkd. by Berry and Akin</p> <p style="margin-left: 40px;">A fir, 26 ins. diam., bears N. 76 1/2° E., 97 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A fir, 18 ind. diam., bears S. 81 1/2° E., 86 lks. dist., with healed blaze.</p>		T 24 S	MC	S 28		S 33		R 7 W		1973
	T 24 S										
MC	S 28										
	S 33										
	R 7 W										
	1973										
	<p>Subdivision of Section 33, T. 24 S., R 7 W., Willamette Meridian, Oregon</p>										
	<p>From the 1/4 sec. cor. of sec. 33 only, on the S. bdy. of the Tp.</p> <p>N. 0° 04' E., on the N. and S. center line of sec. 33.</p> <p>Descend 35 ft. over NW. slope.</p>										
6.65	Bottom of descent, slopes W.; asc. 35 ft. over SW. slope.										
11.05	Dirt road, 15 lks. wide, bears E. and W.										
11.60	Ridge, bears N. 30° W. and S. 30° E.; desc. 535 ft. over broken NE. slope.										
30.00	Creek, 2 lks. wide, course N. 15° W.; desc. 85 ft. over broken NW. slope.										
36.75	Creek, 2 lks. wide, course W.; asc. 35 ft. over SW. slope.										
39.85	Spur, slopes N. 40° W.; desc. 5 ft. over NW. slope.										
40.13	Point for the center 1/4 sec. cor. of sec. 33, at intersection with the E. and W. center line. <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-left: 100px;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td></td><td>T 24 S</td><td>R 7 W</td></tr> <tr><td></td><td>C 1/4 S</td><td>33</td></tr> <tr><td></td><td></td><td>1979</td></tr> </table> </div> <p>from which</p>		T 24 S	R 7 W		C 1/4 S	33			1979	
	T 24 S	R 7 W									
	C 1/4 S	33									
		1979									