

County Surveyor's Record, Douglas County, Oregon

16661

T. 29 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of a portion of the north boundary and subdivisional lines, and subdivision of sections 3, 23, and 33, township 29 south, range 7 west, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey is as follows:

The boundaries of the township and a portion of the subdivisional lines were surveyed by Nathaniel Ford, in 1854.

A portion of the east and south boundaries of the township was resurveyed and the remaining subdivisional lines were surveyed by Roy T. Campbell, in 1910.

The west boundary, a portion of the north and south boundaries and subdivisional lines, and boundaries of certain Donation Land Claims were resurveyed by Fred Mensch, in 1924.

The boundaries of section 9 were resurveyed and the section was subdivided by Hans W. Thielsen, in 1955.

A portion of the east boundary of the township and subdivisional lines was resurveyed by Hans W. Thielsen, in 1957. A portion of this resurvey was cancelled by authority of Director's memorandum 9182 (420) dated August 31, 1970.

A portion of the east boundary of the township and subdivisional lines was resurveyed by Hans W. Thielsen, in 1959.

A portion of the subdivisional lines and the boundaries of Donation Land Claim Number 46 were resurveyed, a portion of the subdivisional lines was corrected and section 21 was subdivided by John M. Jelley, in 1966.

A portion of the south boundary of the township and subdivisional lines was resurveyed by Harvey E. Wofford, G. Steven Popken, and James J. Carlson, in 1974-76.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated December 8, 1980, for Group Number 1044, Oregon.

The directions of the lines were determined by deflection angles turned from azimuths obtained by direct solar observations.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. Only those lines bounding or crossing public lands were blazed. All lines not forming closures were measured twice to preclude error.