

County Surveyor's Record, Douglas County, Oregon

16662

T. 29 S., T. 7 W., Willamette Meridian, Oregon

CHAINS

The geographic position of the 1/4 section corner of sections 2 and 3, as determined by a direct tie to United States Coast and Geodetic Survey triangulation station "TWO OAKS", is as follows:

Latitude 43° 04' 41.9" N. Longitude 123° 30' 14.2" W.

The mean magnetic declination is 19° 00' E.

Dependent Resurvey of a Portion of the North Boundary,
T. 29 S., R. 7 W., Willamette Meridian, Oregon

(Restoring the survey by Nathaniel Ford,
U. S. Deputy Surveyor, 1854)

Beginning at the cor. of secs. 2, 3, 34, and 35, perpetuated by person(s) unknown, recorded by Oscar F. Thiel, Deputy County Surveyor, in 1899; recorded by Arthur Boyer, Registered Engineer No. 1581, in 1957; recorded by James W. Byron, Deputy County Surveyor, in 1961; recorded by Clell Goodwin, Deputy County Surveyor, in 1975; recorded by William J. Ruppert, Registered Land Surveyor No. 866, in 1978; and recorded by Glenn S. Baughman, Registered Land Surveyor, No. 536, in 1980, monumented with a steel axle, 1 1/2 ins. diam., firmly set, projecting 5 ins. above ground, from which the only remaining original bearing tree:

An oak, 42 ins. diam., bears N. 73° E., 200 lks. dist., with opened and burned blaze, no marks visible.

and a bearing tree recorded by Boyer, Byron, Goodwin, and Ruppert

An oak, 38 ins. diam., bears N. 25 3/4° W., 621 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T	28	S	R	7	W
	S	34	S	35	
	S	3	S	2	
	T 29 S				
	1981				

from which

An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument bears N. 47 1/2° E., 84 lks. dist., with brass cap mkd. RM T28S R7W S35 55.6' to COR 1981 and an arrow pointing to the corner.

An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 37° E., 105 lks. dist., with brass cap mkd. RM T29S R7W S2 69.3' to COR 1981 and an arrow pointing to the corner.