

County Surveyor's Record, Douglas County, Oregon

16663

Dependent Resurvey of a Portion of the North Boundary,
T. 29 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 46° W., 10 lks. dist., with brass cap mkd. RM T29S R7W S3 6.6' to COR 1981 and an arrow pointing to the corner.

An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 33° W., 10 lks. dist., with brass cap mkd. RM T28S R7W S34 6.6' to COR 1981 and an arrow pointing to the corner.

Reset axle alongside iron post.

Corner is located on W. shoulder of gravelled road, 40 lks. wide, bears generally N. and S., and in a woven wire fence, extending N. and S.

N. 87° 04' W., bet. secs. 3 and 34, marking and blazing the true line.

Descend 80 ft. over rolling SW. slope, through open pasture land.

7.10 McNabb Creek 10 lks. wide, course N. 50° W.; asc. 5 ft. over NE. slope.

14.85 Woven wire fence, extends N. 20° E. and S. 20° W.

19.47 Point for the E 1/16 sec. cor. of secs. 3 and 34.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16 $\frac{S\ 34}{S\ 3}$
1981

from which

A twin oak, 36 ins. diam., bears N. 29° W., 27 lks. dist., mkd. E 1/16 S34 BT.

A fir, 16 ins. diam., bears S. 36 1/4° E., 56 lks. dist., mkd. E 1/16 S3 BT.

Corner is located 14 lks. S. of woven wire fence line, extending E. and W.

Ascend 25 ft. over NE. slope.

20.40 Woven wire fence, extends N. 75° W. and S. 70° E.

24.55 Top of ascent, slopes N.; desc. 35 ft. over broken NW. slope.

28.45 Woven wire fence, extends N. 45° E. and S. 40° W.

33.75 Creek, 10 lks. wide, course N. 10° E.; asc. 10 ft. over NE. slope.

34.45 Woven wire fence, extends N. and S. 5° W.

38.94 The 1/4 sec. cor. of secs. 3 and 34, reestablished by proportionate measurement and recorded by Arthur Boyer, Registered Engineer No. 1581, in 1957; perpetuated and recorded by Willam J. Ruppert, Registered Land Surveyor