

# County Surveyor's Record, Douglas County, Oregon

16664

Dependent Resurvey of a Portion of the North Boundary,  
T. 29 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

No. 866, in 1978; recorded by Glenn S. Baughman, Registered Land Surveyor No. 536, in 1980, and is accepted as the best available evidence of the position of the original corner, monumented with an iron rod, 3/4 in. diam., firmly set, projecting 4 ins. above ground, from which bearing trees mkd. by Boyer:

An oak, 50 ins. diam., bears N. 32° E., 383 lks. dist., with illegible scribe marks visible on bark blaze.

An oak, 50 ins. diam., bears N. 59° E., 388 lks. dist., with scribe marks BT visible on partially healed blaze.

An oak, 16 ins. diam., bears S. 79 1/2° E., 445 lks. dist., with healed blaze.

An oak, 20 ins. diam., bears N. 42 3/4° W., 583 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 38 ins. in the ground, directly over iron rod, the top 10 ins. below the surface of the ground, with brass cap mkd.

T 28 S R 7 W  
1/4 S 34  
S 3  
T 29 S  
1981

Corner is located in open pasture land.

Land, rolling hills.

Soil, sandy clay.

Timber, fir, ash, oak, willow, maple, and madrone; undergrowth, Oregon grape, blackberry, poison oak, salmonberry, salal, and fern.

Dependent Resurvey of a Portion of the Subdivisional Lines  
T. 29 S., R. 7 W., Willamette Meridian, Oregon

(Restoring the survey by Nathaniel Ford, U. S. Deputy Surveyor, in 1854, the survey by Roy T. Campbell, U. S. Deputy Surveyor, in 1910, the resurvey by Fred Mensch, U. S. Cadastral Engineer, in 1924, the resurveys by Hans W. Thielsen, Cadastral Surveyor in 1955, 1957, and 1959, and the resurvey by Harvey E. Wofford, G. Steven Popken, and James J. Carlson, Cadastral Surveyors, in 1974-76)

From the 1/4 sec. cor. of sec. 27 only, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

1/4  
S 27  
1924

from which bearing trees mkd. by Mensch