

# County Surveyor's Record, Douglas County, Oregon

16666

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 29 S., R. 7 W., Willamette Meridian, Oregon

**CHAINS**

Timber, ash, maple, yew, pine, oak, fir, alder, cedar, hemlock, and chinquapin; undergrowth, poison oak, fern, blackberry, salmonberry, huckleberry, Oregon grape, salal, arrowwood, rhododendron, hazel, and young timber.

From the cor. of secs. 23, 24, 25, and 26, perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1969, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 29 S R 7 W

S 23 | S 24

S 26 | S 25

1969

from which the remains of the original bearing trees

A root hole, bears N. 88 1/2° E., 44 lks. dist., with a down madrone alongside, 40 ins. diam., no marks visible. (Record, N. 84 1/2° E.)

A sawed fir stump, 24 ins. diam., bears S. 57° E., 41 lks. dist., with healed blaze. (Record, S 54 3/4° E.)

A sawed fir stump, 28 ins. diam., bears N. 16 1/2° W., 29 lks. dist., with illegible scribe marks visible on decayed blaze.

and the remains of bearing trees mkd. by Powell

A sawed fir stump, 20 ins. diam., bears N. 59° W., 122 lks. dist., with healed blaze.

A fir, 36 ins. diam., bears N. 21° W., 177 lks. dist., with healed blaze.

and the remains of a bearing tree recorded by Powell

A sawed fir stump, 13 ins. diam., bears N. 84° W., 23 lks. dist., with illegible scribe marks visible on burned blaze.

and a new bearing tree

A fir, 14 ins. diam., bears N. 58° W., 166 lks. dist., mkd. T29S R7W S23 BT.

No other suitable trees available within limits.

S. 89° 53' W., bet. secs. 23 and 26.

Descend 205 ft. over SW. slope, through heavy timber and dense undergrowth.

11.70 Head of ravine, drains S. 25° W.; desc. 10 ft. over SW. slope.

12.95 Spur, slopes SW.; desc. 385 ft. over SW. slope.

32.50 Creek, 4 lks. wide, course SW.; asc. 40 ft. over SE. slope.