

County Surveyor's Record, Douglas County, Oregon

16667

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

40.16

The 1/4 sec. cor. of secs. 23 and 26, monumented with the original unmarked basalt stone, 15 x 12 x 6 ins., firmly set, projecting 6 ins. above ground, alongside of which is an iron pipe, 1 1/2 ins. diam., firmly set, projecting 6 ins. above ground, from which the remains of the original bearing trees:

A madrone, 36 ins. diam., bears N. 46° E., 139 lks. dist., with scribe marks 1/4 S BT visible on open blaze.

A sawed fir stump, 27 ins. diam., bears S. 64 3/4° W., 62 lks. dist., with healed blaze.

and the remains of a bearing tree of which I have no record

A cedar snag, 36 ins. diam., bears S. 25° E., 26 1/2 lks. dist., with scribe marks 1/4 S BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W

1/4 $\frac{S\ 23}{S\ 26}$

from which new bearing trees

A fir, 11 ins. diam., bears N. 19° E., 12 1/2 lks. dist., mkd. 1/4 S23 BT.

A fir, 9 ins. diam., bears S. 49 1/2° E., 6 lks. dist., mkd. 1/4 S26 BT.

Deposit corner stone and reset iron pipe alongside iron post.

S. 89° 56' W., beginning new measurement.

Ascend 5 ft. over SE. slope.

0.45 Spur, slopes S. 40° W.; desc. 235 ft. over SW. slope.

14.15 Creek, 5 lks. wide, course S. 40° W.; asc. 10 ft. over broken SE. slope.

20.40 Spur, slopes S. 10° E.; desc. 95 ft. over SW. slope.

27.95 Ravine, drains S. 20° W.; asc. 5 ft. over SE. slope.

28.85 Spur, slopes S. 5° E.; desc. 150 ft. over broken SW. slope.

39.55 Creek, 7 lks. wide, course S. 50° W.; asc. 5 ft. over SE. slope.

40.03 The cor. of secs. 26 and 26 1/2 only, perpetuated and re-recorded by Ben B. Irving, Deputy County Surveyor, in 1938, monumented with the original basalt stone, 9 x 6 x 6 ins. (record, 15 x 12 x 10 ins.), firmly set, projecting 5