

# County Surveyor's Record, Douglas County, Oregon

16670

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 29 S., R. 7 W., Willamette Meridian, Oregon

**CHAINS**

A maple stump, 20 ins. diam., bears N. 17 1/2° E.,  
39 1/2 lks. dist., with illegible scribe marks  
visible on open blaze.

and new bearing trees

A grand fir, 9 ins. diam., bears N. 42 1/2° E., 94 lks.  
dist., mkd. 1/4 S23 BT.

A fir, 6 ins. diam., bears S. 34 3/4° E., 28 lks.  
dist., mkd. 1/4 S23 BT.

N. 0° 27' E., bet. secs. 22 and 23.

Descend 25 ft. over NW. slope, through heavy timber and  
dense undergrowth.

1.96 The 1/4 sec. cor of sec. 22 only, perpetuated and recorded  
by James W. Byron, Deputy County Surveyor, in 1962, monu-  
mented with an iron post, 1 in. diam., firmly set,  
projecting 8 ins. above ground, with brass cap mkd.

1/4 |  
S 22 |  
1924

from which the remains of a bearing tree mkd. by Mensch

A fir stump, 16 ins. diam., bears S. 23° W., 72  
lks. dist., with illegible scribe marks visible  
on opened blaze.

and bearing trees mkd. by Byron

A fir, 20 ins. diam., bears South, 44 lks. dist.,  
with healed double blaze.

A fir, 14 ins. diam., bears N. 72° W., 41 lks.  
dist., with healed double blaze.

N. 0° 27' E., beginning new measurement.

Descend 140 ft. over NW. slope.

6.70 Creek, 1 lk. wide, course N. 55° W.; asc. 15 ft. over  
SW. slope.

9.10 Spur, slopes N. 55° W.; desc. 65 ft. over NW. slope.

16.50 Ravine, drains S. 85° W.; asc. 5 ft. over broken SW.  
slope.

17.10 Spur, slopes N. 35° W.; desc. 10 ft. over NW. slope.

18.02 Point for the N 1/16 sec. cor. of sec. 23 only.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.  
in the ground, with brass cap mkd.

| N 1/16  
| S 23  
1981

from which