

# County Surveyor's Record, Douglas County, Oregon

16672

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 29 S., R. 7 W., Willamette Meridian, Oregon

**CHAINS**

From the 1/4 sec. cor. of sec. 23 only, monumented with an iron post, 1 in. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd.

1/4 S 23  
1924

*FND OK  
4/91 M113-6*

from which bearing trees mkd. by Mensch

A fir, 22 ins. diam., bears S. 11° E., 42 lks. dist., with healed blaze.

A white oak, 9 ins. diam., bears S. 34° W., 51 lks. dist., with healed blaze.

N. 89° 39' W., bet. secs. 14 and 23.

Descend 40 ft. over SW. slope, through heavy timber and dense undergrowth.

3.57 The 1/4 sec. cor. of sec. 14 only, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1962, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

1/4 S 14  
1924

*FND OK  
4/91 M113-6*

from which a bearing tree mkd. by Mensch

A fir, 17 ins. diam., bears N. 60° E., 68 lks. dist., with healed blaze.

and a bearing tree mkd. by Byron

A fir, 16 ins. diam., bears N. 76° W., 31 lks. dist., with healed double blaze.

S. 89° 50' W., beginning new measurement.

Descend 140 ft. over SW. slope.

16.41 Point for the W 1/16 sec. cor. of sec. 23 only.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 S 23  
1981

from which

A fir, 5 ins. diam., bears S. 25 1/4° E., 45 lks. dist., mkd. X BT.

A fir, 9 ins. diam., bears S. 27° W., 33 lks. dist., mkd. W 1/16 S23 BT.

Descend 30 ft. over SW. slope.

27.05 Creek, in culvert, 3 lks. wide, course S. 25° W., also dirt road, 15 lks. wide, bears N. 45° E. and S. 85° W.; continue over nearly level land.

28.40 Spur, slopes S. 5° W.; desc. 30 ft. over SW. slope.